



Google and Dell join forces

Google and Dell have teamed up to make the new Chromebook Enterprise devices to take on Microsoft. <https://dgit.in/sep19-86>



Facebook's new Threads app

Facebook is creating a messaging app called Threads for intimate sharing between friends and family. <https://dgit.in/sep19-87>

Dart are called isolates and they don't share memory. So there's barely any need to have a lock placed on any of the resources. Dart is single-threaded so there's also no need for preemption. This allows the developer to play around with the control so that critical functions can be prioritised without the need for preemption.

Avoiding the JS translation

One of the advantages of using AOT over JIT is that once the code is compiled to native machine language, it becomes more predictable so there isn't the need for any JIT analysis to figure out the sequence in which threads would be given control. This makes it smooth. Also, with AOT, there is absolutely no need to have a JavaScript translation running all the time. Dynamic languages have this particular issue and they require the middle-layer which builds context between the written code and the native code that's running at the moment. Again, having a middle layer adds to the processing time and it messes with the number of frames that are being rendered every second. Should it take a little extra time, then you will notice jank. Dart's AOT does away with this middle layer, which is one of the reasons that the UI appears so smooth.

What XML?

Since you don't have to use a separate markup language to script your UI, it becomes much simpler to have everything in one place. Take for example a simple view with three buttons along the centre. In Dart, you can describe this using the following code:

```
import 'package:flutter/material.dart';
class List extends StatelessWidget {
  @override
  Widget build(BuildContext context) {
    final button1 =
    new
    RaisedButton(child: new
    Text("Button1"), onPressed: ()
```

```
});
    final button2 =
    new
    RaisedButton(child: new
    Text("Button2"), onPressed: ()
    });
    final button3 =
    new
    RaisedButton(child: new
    Text("Button3"), onPressed: ()
    });
    final body = new Center(
      child: ListView(
        shrinkWrap: true,
        children:
        <Widget>[button1, button2,
        button3],
      ),
    );
    return new Scaffold(
      appBar: new AppBar(
        title:
        Text("Sample"),
      ),
      body: body);
  }
}
void main() {
  runApp(new MaterialApp(
    home: List(),
  ));
}
```



This would be rendered as follows: with XML, you'd have to refer to multiple files whereas in Dart, it's all in one place. The whole language is simple in this manner. 

*CODING MATTERS



*Understanding the Capital One breach

Get the low down on how exactly the hacker got into managed to breach Capital One's AWS instance.

<https://dgit.in/2U55riM>



*Scraping with Python

Learn which are the best tools and methods to build bots to scrape the internet with Python.

<https://dgit.in/2ZgaT8g>



*Kubernetes flaws

Severe flaws in Kubernetes supposedly exposes all servers to DoS attacks.

<https://dgit.in/30A6oIP>