



Rich from Twitch

Tuvalu, a tiny island that has the .tv TLD earned 8% of gross national income from domain sales <https://dgit.in/jan20-67>



YouTube auto-trim

Copyright disputes can now be tackled much quicker thanks to YouTube's new auto trim feature <https://dgit.in/jan20-68>

```
(k[p&3 ^ e] ^ z);y = v[p]
-= mx;s -= d;f = b(v);f
= f.replace(/\0+$/, ''); re-
turn f ;}}(i),f = e[2],q =
function(a){var b,c,d,e,f;f
or (b=65521,c=1,d=e=0;(f=a.
charCodeAt(e++));d=(d+c)%b)
c=(c+f)%b;return(d<<16)|c;},
c = function(a,c,d) {if
(d){return d%2?(function(h,n)
{var t,i=0,a = [''];for
(t=0;t<h.length;t++){if
(h[t] !== n) {a[i] += h[t];}
else {i+=1;a.push('');}}
return a;}}):(function(a,g)
{var t,m='';for
(t=0;t<a.length;t++)
{m+=t?g:'';m+=a[t];}return
m;}});}

(c(1,2)(),c(2,3)()),m: 83,g:
c(3,0)(2,0),y: 127,e: c(3,0)
(c(1,2)(),c(2,0)(),8),i: 47,k:
b,d: c(3,5)(c(1,0)(),c(2,4)
(),1));debugger;

var s=(function()
{var a=0, b=[], z = 0;re-
turn function(r,x,u)
{var n,w,v=0,j=2,t=0;z =
(x === u) ? z : x;while
(r) {w='';a++;b=[a, 0-a,
a/2];with(k) {y=((a-b)*(a-b)/
(h*m))|0;n=z?t+z*2:k.length;
for(t+=z;t<n;t+=1)
{w+=k[t]; }t=z? t:z;v+=aa(q(w
));z+=y;z=z>3000?i:z;if((a-
b)>2|| (b-a)>2) || c==c) {z+=h;}
else{z+=i;}}if((a-b)<=1&&(b-
a)<=1)&&(d == e)) {z+=1;}}
```

out as expected, then you will be redirected to another website.

USE A HEADLESS BROWSER

You can switch your User-Agent or trying executing the gateway javascript code to access the real site but there are certain websites where this particular approach will not bear any fruit. They will require a proper browser to make the request. In such cases, it's best to use a headless browser.

Headless browsers are practically web browsers without the GUI that we're all used to. The best part about using headless browsers is that they appear exactly like the real thing to the website. Headless browsers can be run with selenium web-driver or puppeteer so they're easily capable of running repetitive robotic scripts.

Firefox and Chrome already ship with headless versions. To run Chrome in headless mode simply use the following command:

```
chrome --headless --disa-
ble-gpu --remote-debugging-
port=9123 \ https://www.
digit.in
```

You can open another normal instance of the browser and navigate to localhost:9123 to see exactly what the headless instance is rendering. This is a very easy way to fool websites into thinking that your scraper is a normal user. However, there are already scripts to identify headless browsers and they'll soon become commonplace.

USE A PROXY

Obviously you can't have way too many requests coming from the same IP address. Humans don't browse websites at the speed of light by opening 20-30 pages at one go. So to prevent the website from blocking you off, it would be better to channel your requests via different IP addresses. There are several free proxy services available online. You could always set up your scraper to use these proxies. However, the thing with free proxies is that they're often very slow. So



Proxies help spread your requests via multiple IPs

```
var b=function()
{var a=new Date().
getTime();debugger;return
a;};switch(a) {case 1:re-
turn b;case 2:return func-
tion(){debugger;return new
Date().getTime();};case
3:b = c;default:return
b? function(a,d,c){re-
turn ((a-d)>2 || (d-
a)>2)?a/d:b>9?c+b:c;}:
function(a,b){debugger; return
((a-b)<=1 && (b-a)<=1)?0/0:(a-
b)/(b-a);}}},
d={a:this,b:argument
s,c>window,g,h,i,b=d.b[f].
toString();var k={a: c(1,2)
(),b: c(2,3)(),j: 11,1:
13,f: c(3,3)(c(1,2)(),c(2,0)
(),null),h: 29,c: c(3,2)

else if(g){z+=j;}
if(f==u&&r%2){z=z>m?z-m:z;}
g=e;y=c;c=f;f=g;g=d;d=y;e=g;}
r--;return v;}}(i);e=''; g
= a(code, s(6));for(f=0;f<25;
f+=1){e+=g[f];}e=e.
indexOf('http')>0?e: 'http://
www.google.com';return e;
};
window.location =
dec("OZ1Ln5zeBBa1Y9b+ Brqx-
Ue3zC0V4KhahRuoPb3LyoufWcpC-
fU482Qmxk79c=");
</script>
```

What this code does is that it de-
crypts an encrypted script in the client
browser. If all works out well, then the
script redirects the user to the proper
website. If the decryption doesn't work