



Samsung doubles down on EUV

Samsung is planning to invest \$116 billion in EUV lithography to further shrink transistors within chips <https://digit.in/jan20-71>



FB to host music vids

Facebook reportedly pursuing rights to show music videos in Facebook Watch. Beta tests in India and Thailand <https://digit.in/jan20-72>

Teardown: DJI Mavic Mini

DJI's smallest, lightest and cheapest drone offering

Dhriti Datta | dhriti@digit.in



Screwed on propeller blades and body shell

The CCW propeller blades are fastened to the individual motors by screws, as is the top and bottom shell of the drone. Opening the battery door gives you access to two additional screws positioned at the edge of the battery tray, which when removed exposes the heatsink for the motherboard. The warranty void sticker is present beneath the battery door.



The system board and processor

With the heatsink removed, the cables are the only thing attaching the motherboard or system board to the chassis. Upon further prying, the motherboard, heat spreaders and the thermal compound can be removed which lets you inspect the drone in detail. The motherboard features an Ambarella processor, which is a step up over previous DJI drones. On the flip side, the same board is seen with an SD card slot.

IMU and GPS module

The IMU/GPS board is screwed on to the frame using a plastic mount. The loom ribbon cable, when carefully released, separates the unit from the frame altogether. After this, soft rubber dampers need to be pried away which connect the GPS/IMU board to the mount.

