



Tech giants avoid paying tax

Amazon, Facebook, Google, Netflix and Apple avoided paying over \$100 billion in taxes over the last decade <https://dgit.in/jan20-73>



Google fined \$166 million

France fined Google \$166 million for abusing their dominant position in the online ad market <https://dgit.in/jan20-74>



Extracting the motors

Sticky-back foam pads cover the screws holding the motors in place. Once removed, the antenna panel can also be released from the leg. If you were to replace the motors altogether, it would need to be de-soldered from the ESC board and then untangled from the antenna wire. The motors are tiny and brushless with fourteen sets of windings that are set on metal mounts.



DJI Mavic Mini



Dismantling the transmitter

Two 1.5 mm hex bolts need to be removed after which the lower plastic strip of the transmitter can be stripped away. After this, undoing a few more screws will let you release the two communication cables. Finally, the front of the transmitter can also be popped off. The transmitter processor board lies under a metal shield. Here, you will find an Atheros AR1021X-CL3D Wi-Fi radio chip.



Camera capable of 2.7K video footage

With the system board out of the way, the gimbal is in view which is fastened it to the frame using four suspended rubber mounts. Unscrewing the cable guide from the top part of the gimbal frees up the camera as well. The Mavic Mini is capable of shooting 2.7 K video at 30 FPS or 1080p video at 60 FPS. The sensor, measuring 1 / 2.3-inch, can capture 12 MP images across several modes. Due to the structural complexity of the camera/gimbal unit, DJI usually replaces them and strays away from repairs.

Images courtesy: RC Geeks
Website: rcgeeks.co.uk
Teardown link: <https://dgit.in/mavicmini>