



Orario in Minecraft

Minecraft team Varuna have recreated Orario from popular anime DanMachi in Minecraft. <https://digit.in/may20-69>



Derpy Turtle

Scientists have discovered a new smug-looking species of Mata Turtle in South America. <https://digit.in/may20-70>

Indoors

Now there are a variety of doors within the house that have locks, but these locks are not really meant for security purposes, as in keeping burglars out. Depending on the type of lock implemented, there are a number of ways of getting access to the rooms inside. A scale or a credit card can

be used to slide along the door frame, or pushed at the lock to open some kinds of locks.

For doors with push button knobs there are three different approaches depending in the mechanism. The most common is to simply use a screwdriver or butter knife in the vertical slit on the door, and turn it like a regular key, while

turning the knob at the same time.

In some bathroom locks, this is actually a safety feature. If the knob has a twist toggle instead of a push button, then a screwdriver or any thin, flat object can be used to open the lock. There is no need to twist the knob, the idea is to untwist the toggle from the other side of the door. If none of these techniques work, then there is still another possibility. Just use a screwdriver, scale or any thin and flat object to simply pry away the doorknob. This should give you access to manipulate the mechanism directly.



Car doors

There are a number of ways to open car doors. The simplest one is to use a scale and simply push down in the slight gap between the glass and the door, and then probe both left and right till the latch pops open. If that does not work, a possible approach is to firmly hold the glass, and exert a downward pressure on it. It is difficult in the beginning, but becomes easier once there is enough of a gap to use your fingers, and then push down from the side of the glass. Even if there is a thin gap between the glass and the top of the car, it is possible to use a shoelace with a slipknot as a noose around the lever to pull it upward and open the door. Now, another old school way of opening car doors is to straighten out a clothes hanger, but keeping the hook. Now, pry apart the lining at the side of the window, and push in the hanger. You have to aim for the latch, which can be guessed based on the location of the handle outside the car door. Once the hook catches, push the hanger or the hook towards the back of the vehicle, which should make the door pop open. This is called jimmying the car door.



Chain locks and bar locks

These come in various forms, and are basically a privacy measure that allows those inside rooms to secure the doors, even against those who may have keys to enter the room or the house. The basic principle for tackling all chain locks is the same, you need to use the door itself as leverage, and for this you need to be aware of the exact angle in which you need to move the chain. For this reason, it is important to have already seen the chain locks before you attempt to break it, so you know the direction of attack. To move the chain, a piece of string can be used, or the shoelace, which is surprisingly useful for getting past locked doors. Loop the shoelace around the chain, and use the top of the door as a fulcrum to move the head of the chain out of the socket. The chain can be moved to the left or the right. Another option is to

use a rubber band, double it up around the latch, and attach both ends to the door handle if there is one. Now, turning the door handle should automatically pop out the chain. If a handle is not available, or not reachable, the doubled up rubber band can be first put around the chain, then both ends stuck to the door with cello tape. Now, when you close the door, the chain should pop out. For all kinds of bar locks, the go to method is to use a piece of card. The latches that open upward, downward or outward can simply be pushed open by moving the card in the right direction. For the latches that open inward, the procedure is a little more tricky. You will have to cut a slit in a piece of card, and then insert it through the gap in the door. Once the slit is placed around the latch, you will have to pull the card towards you, to make sure that the bar is not in the way when you open the door.

