



Pay for movies with crypto

AMC theaters start accepting cryptocurrency payment for movie tickets.
<https://digit.in/dec21-03>



Twitch on Switch

Twitch is now officially available on a Nintendo console - the Nintendo Switch.
<https://digit.in/dec21-04>

softwareupdate --install-rosetta

- Your Node.js version should be between 10 and 14 to run the npm installer. Use nvm for managing node versions with ease.
- Make sure your Windows version is 7+.
- If there are performance issues, try disabling your antivirus.
- For iOS development, latest version of Xcode should be installed.
- Meteor npm is not to be installed in the project's package.json at all.

Now that we are past the initial checks, let's go ahead and run the following command in our terminal to install the latest official Meteor release.

```
npm install -g meteor
```

Notes:

- The -g parameter simply instructs npm to install meteor globally. If you wish to maintain and organise your packages, remove the -g flag.
- Windows users can utilise Windows Developer Mode to run the installer faster.
- Apple M1 computers will need the arch -x86_64 Rosetta prefix as follows:

```
arch -x86_64 npm install -g meteor
```
- If you are running Linux, and are getting permission issues, use sudo, and the --unsafe-perm flag. Only use this if you know what you are doing.
- For an alternative method of installation on Linux, one that is not node or npm dependent, the following command can be run. This method is not recommended as Meteor is node dependent, and any issues with the node installation should be resolved first:

```
curl https://install.meteor.com/ | sh
```

Congratulations! We now have Meteor successfully installed! To immediately get a project up and

running, open a new terminal window and type the following:

```
meteor create yourappname
```

Where "yourappname" is well, the name of your app (go figure).

To run this app, run the following commands:

```
cd yourappname
meteor npm install
meteor run
```

The console should output the URL for the locally hosted server.

Creating a dummy to-do list app:

To demonstrate the various features of Meteor and how to develop using it, we will be building a simple To-Do List App. For the purposes of this tutorial, we will be sticking with React, but keep in mind it is just as easy to shift to any other frontend js framework.

We can create our project files with the following command:

```
meteor create --react simple-todos-react
```

Note that the --react flag is the default flag, and can be removed as well if needed.

This will create all the relevant project files. The client directory has all the client side files, including the client/main.jsx file which allows Meteor to render the app main component into HTML. The server directory correspondingly has all the server relevant files, the primary focus of which is our server/main.js, which will initialise our MongoDB database. Meteor will automatically install and embed MongoDB into the project, so there is no need to install it externally.

The app can now be run using:

```
meteor run
```

This is a good time to browse through all the directories and files

created by Meteor. All of the frontend React code will be available in the import/ui directory. The root component of the app will be the App.jsx file.

Scaling app viewport for mobile devices

A first quick adjustment we can make before starting development is going to the client/main.html file, and making the following changes inside the head tag:

```
<meta charset="utf-8"/>
<meta http-equiv="x-ua-compatible" content="ie=edge"/>
<meta
  name="viewport"
  content="width=device-width, height=device-height, viewport-fit=cover, initial-scale=1, maximum-scale=1, minimum-scale=1, user-scalable=no"
/>
<meta name="mobile-web-app-capable" content="yes"/>
<meta name="apple-mobile-web-app-capable" content="yes"/>
```

This will ensure the app is perfectly usable on smaller devices well, and scales according to the platform it is being developed for.

Adding and enabling Dev Error Overlay

This is also a good point to add the package dev-error-overlay. To to this simply run:

```
meteor add dev-error-overlay
```

We can now see the errors on the browser directly and not just on the console. These will reflect on rebuilding the app. The hot-module-replacement package, which Meteor adds by default when using React, will allow for the app to be rebuilt and only the modified packages updated while it is running. This will considerably speed up development time.