



OnePlus teases the Nord N20
OnePlus gave PCMag an official render of the device, along confirmed SuperVOOC fast charging <https://dgit.in/apr22-39>



Auto-Summaries in Google Docs
Google Docs now automatically generates suggestions to aid writers in creating content summaries. <https://dgit.in/apr22-40>

Two's a trouble

A friend wants two ISPs at home but without the hassle of more hardware

Agent001 | agent001@digit.in



O

ne of the changes that a lot of us made to our homes at the beginning of the pandemic was to get

better internet services. While I've personally had two ISPs for ages, a lot of my friends were only recently getting onto the multi-ISP bandwagon. And with that, began the incessant calls. You see, each ISP tends to favour their own CPE (Customer Premises Equipment) for the set up process while a few are open to using the existing routers that users have. So, folks would have to either give up one of their connections if they wanted to keep just one router in their homes, or have two routers at the same time and switch between internet connections on the fly. Don't even get me started on fibre connections since there's the additional GPON device aside from the router. This means that people might end up with one-to-four devices at their homes. And if you wanted to use both ISPs on all computers, then it was a completely different challenge. Thankfully, I had already tackled these issues more than a decade ago.

One solution is to have a switch connection to the LAN ports of both routers and then let other devices get onto the switch. This way, all LAN clients can pick between either ISP.

But what happens to wireless clients? They still have to switch manually between the two routers. And there's no telling if the LAN clients can see the router clients because there's a likelihood of subnet mismatch. There's a lot more that can go wrong but you can see how much of a hassle it is with such a setup.

The more optimal solution is to use a master/slave or parent/child setup. Here's how you can go about



it. You've got two ISPs supplying internet to your home with each internet connection being channelled via a separate router. Let's call the first router as Gateway-1 and the second one as Gateway-2. Both routers are already set up by the ISP.

First, figure out the LAN IP ranges for both routers. Usually, routers are given the IP 192.168.1.1 or 192.168.0.1. Flipping the router or reading the

manual will let you know what IP each router has. We're going to designate Gateway-1 as the parent or main router. So it remains completely unchanged. Let's assume that the IP for Gateway-1 is 192.168.1.1. Now access the control panel of Gateway-2 and set its IP to 192.168.1.2. Next, go to the LAN settings and find a setting called DHCP and disable it in Gateway-2. DHCP is the protocol that decides the IP address that needs to

be given to each device that's connected to it.

Now, connect a LAN port from Gateway-2 to the LAN port of Gateway-1. This ensures that all devices connected to Gateway-2 will rely on the DHCP service in Gateway-1 to get their IP address. So no matter which gateway you connect

your new device to, it will have to get the IP from the same router, which is Gateway-1.

That's it. That's just the hardware configuration that you had to make. Now, all the configuration happens on the client side. If you have multiple devices at home and want to designate which gateway or ISP a particular device should connect to, then open the network settings and