```
print ("URL of Main image")
print(article.top_image.src)
```

The output is:

```
Title:
Ionic: A UI Framework to Simplify Hybrid Mobile App
Development
```

The meta description is:

```
Ionic makes the task of creating hybrid apps very easy, and
these can be ported to various platforms.
```

First *n* characters of the cleaned text

```
This article present
```

URL of main image

```
http://opensourceforu.com/wp-content/uploads/2016/01/Figur-1-
350x390.jpg
```

Textract

The Web includes resources apart from HTML pages. Textract is a library to extract data from those resource file formats. In simple terms, it can be described as a library to extract text from any type of file—from resources such as Word documents, PowerPoint presentations, PDFs, etc. Textract attempts to extract text from gif, jpg, mp3, ogg, tiff, xls, etc, and has various dependencies to handle these file formats. To install it, use the following commands:

```
apt-get install python-dev libxml2-dev libxslt1-dev antiword
unrtf poppler-utils pstotext tesseract-ocr flac ffmpeg lame
libmad0 libsox-fmt-mp3 sox

pip install textract
```

The extraction of text is carried out with the *textract.process()* function. The text extraction from the image shown in Figure 3 can be carried out with the following simple program:

```
import textract
text = textract.process("oa.jpg")
print text
OPEN aACCESS
```

The Textract extraction process depends upon the quality of the source document. Though it is not guaranteed to extract 100 per cent correct text from all the sources, it provides an insight into the type of content residing in the resource, which is definitely key information to have in many scenarios.

To summarise, this article aims to provide an eye-opener to the domain of content extraction from the Web. Though the above-mentioned libraries provide powerful functions for the content extraction process, they do pose research level challenges. Interested developers could take these up and provide better solutions. END

References

[1] *https://github.com/Alir3z4/html2text/blob/master/docs/index.md*
[2] *https://lassie.readthedocs.io/en/latest/*
[3] *http://newspaper.readthedocs.io/en/latest/*
[4] *https://github.com/grangier/python-goose*
[5] *https://github.com/deanmalmgren/textract*

By: Dr K.S. Kuppusamy

The author is assistant professor of computer science at the Pondicherry Central University. He has more than 10 years of teaching and research experience in academia and industry. His interests include accessible computing, Web information retrieval, mobile computing, etc. Reach him via mail at *kskuppu@gmail.com.*

Continued from page 86...

- clicking on an element

For example:

```
$("button").click(function(){
  // code goes here...
});
```

Making an AJAX request by jQuery

AJAX stands for Asynchronous JavaScript and XML. It is used to exchange data with a server, and to update parts of a Web page without reloading the entire page.

Two commonly used methods for a request-response between a client and server in jQuery are GET and POST:

1. *$.get();*
2. *$.post();*

For example:

```
$("button").click(function()
{
var url_to_hit  = 'https://www.google.co.in/';
    $.get(url_to_hit, function(data, status)
{
        $('#anyElementId').html(data);  // update any div you
want with reloading
    });
});
```

END

By: Neha Ahlawat

The author likes coding and is always interested in learning new technologies. She can be contacted at *nehuahlawat@gmail.com.*