

```
ps aux | awk '{print $8 ~ " $2"}' | grep -w Z
```

You will get an output like what's shown below:

```
Z 6780
Z 8976
```

Here, 6780 and 8976 are zombie process IDs.

You can check the program associated with the process using the `ps` command and kill the process if required.

If you want to display the process that is consuming more resources, here is the command:

```
top | head -n 8 | tail -n 1
```

—Bharathiraja, pbrthemaster@gmail.com

Moving quickly from anywhere, with \$CDPATH

Do you know the environment variable `$CDPATH`? It lets you define some path to look for directories when moving with the command `CD`. You can define multiple paths in this variable. This can be useful if you have some directories that you access more frequently than others. As this variable defines the order that you move from one directory to another, I suggest you to keep the `~` directory in the first position of your variable declaration. Of course, you can set this variable in your `~/bashrc`.

```
smart@grimm:~$ export CDPATH=.:~/
smart@grimm:~$ cd usr
/usr
smart@grimm:~/usr$ cd Desktop
/home/nicolas/Desktop
```

—Remin Raphael, remin13@gmail.com

Hardware info on live systems

The `dmidecode --type memory` command is used to know the type of RAM and its speed without opening your computer. It can also be used to get to know details about the BIOS, motherboard, processor, cache, slots, etc. If we want to get information about the BIOS, use the following command:

```
dmidecode --type bios
```

For cache, use:

```
dmidecode --type cache
```

...and so on.

—Elvise James, elvisejames@gmail.com

Create a directory with different permissions

When we need a directory with specific permissions, we generally create the directory using the `mkdir` command and then set the required permissions using `chmod`.

Did you know you define the access permissions while creating the directory itself? Try the following command:

```
[root@server ~]# mkdir /root/test1 -v -m 1777
mkdir: created directory '/root/test1'
```

...where we have used the `-m` flag to define the permission we need to set (in our case it's 1777, that is read, write and execute permissions for the directory are given to everyone), and `-v` stands for verbose mode.

Now, you can check the directory permission by a simple `ls` command as follows:

```
[root@server ~]# ls -lhd /root/test1
drwxrwxrwt 2 root root 4.0K Jul 29 01:42 /root/test1
```

—Govindarajulu govind.rajulu@gmail.com

Save complex documents from any source

Latest versions of GNOME and KDE (along with CUPS) support creating PDF files out of any printable document. This facility can be used to save any printable document as a PDF file.

1. Select the printing option, usually *File→Print...*, in the application hosting the document.
2. Select the PDF option as the printer name in the dialogue box—*Print to File/PDF*.
3. If applicable, type a file name, set output options, and click *Print*.

This process is very useful for quickly saving dynamically-generated Web pages such as e-mails, confirmation forms, reports, etc.

—Saurav Sengupta, saurav.mailbox@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.