

EPiA-N700 Nano Series Motherboard



- VIA C7, 1GHz or VIA Eden™ 500 MHz Processor
- Supports upto 2GB DDR2 SODIMM, Onboard 1 IDE & 2 SATA port
- 3D/2D Graphics With MPEG 2 & 4, WMV9 decoding Acceleration,
- Supports CRT, LVDS, DVI & supports HD Audio
- 4 Serial, 4 USB & Gigabyte Lan interfaces
- Supports Compact Flash Card
- Single 12V DC Supply, Low profile Design

EPiA-P700 Pico Series Motherboard



- Revolutionary Form Factor
- VIA C7, 1GHz or VIA Eden™ 500 MHz Processor
- 3D/2D Graphics With MPEG 2 & 4, WMV9 decoding Acceleration,
- Supports CRT, LVDS, DVI & has Gigabyte Lan interface
- Com Port, 4 USB & supports HD Audio
- Single 12V DC Supply, Low profile Design

EPiA-M700 Mini-ITX Series Motherboard



- VIA C7, 1.8 GHz (with Fan) or 1GHz (Fanless)
- Supports upto 2GB DDR2 DIMM, Onboard 1 IDE & 2 SATA ports
- HC DX9 3D/2D Graphics With MPEG 2 & 4, WMV9 decoding Acceleration,
- Supports CRT, LVDS, DVI & supports HD Audio
- 2 Serial, 6 USB & Dual Gigabyte Lan interfaces
- Supports Compact Flash Card
- Designed For High End Digital Signage & Kiosk Applications

AMHEDABAD Tel.: +91 - 79 - 2687 1977 / 2988
BANGALORE Tel.: +91 - 80 - 2527 4390 / 2525 0220
HYDERABAD Tel.: +91 - 40 - 2774 1122 / 2772
NEW DELHI Tel.: +91 - 11 - 2671 2358
PUNE Tel.: +91 - 20 - 2563 1081 / 6601 1818



DYNALOG
(INDIA) LIMITED

www.dynalogindia.com

H.O.: Kailash Vaibhav, Parksite,
 Vikhroli (West), Mumbai - 400 079
Tel. : +91 - 22 - 25181900 (16 lines)
Fax : +91 - 22 - 2518 1930 / 40
E-mail : sales@dynalogindia.com