

```
import android.widget.Button;
import android.widget.EditText;
import android.util.Log;
import android.view.View;
import android.view.View.OnClickListener;

public class makeacall extends Activity {

    EditText mEditor;

    /** Called when the activity is first created. */
    @Override
    public void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.main);
        mEditor = (EditText) findViewById(R.id.EditTextPhoneNumber);

        /**
         * A call-back for when the user presses the number buttons.
         */
        OnClickListener mDialPadListener = new OnClickListener() {
            public void onClick(View v) {
                StringBuffer previousNumber = new StringBuffer(mEditor.
getText().toString());
                CharSequence phoneDigit = ((Button)v).getText();
                mEditor.setText(previousNumber.append(phoneDigit));
            }
        };

        /**
         * A call-back for when the user presses the call button.
         */

        OnClickListener mPhoneCallListener = new OnClickListener() {
            public void onClick(View v) {
                call(mEditor.getText().toString());
            }
        };

        // Hook up button presses to the appropriate event handler.
        ((Button) findViewById(R.id.Button00)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button01)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button02)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button03)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button04)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button05)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button06)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button07)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Button08)).setOnClickListener(mDialPa
```

```
dListener);
        ((Button) findViewById(R.id.Button09)).setOnClickListener(mDialPa
dListener);
        ((Button) findViewById(R.id.Buttonstar)).setOnClickListener(mDialP
adListener);
        ((Button) findViewById(R.id.Buttonhash)).setOnClickListener(mDial
PadListener);

        ((Button) findViewById(R.id.ImageButtonDial)).setOnClickListener(m
PhoneCallListener);
    }

    private void call(String phoneNumber) {
        try {
            Intent callIntent = new Intent(Intent.ACTION_CALL);
            callIntent.setData(Uri.parse("tel:" + phoneNumber));
            startActivity(callIntent);
        } catch (ActivityNotFoundException activityException) {
            Log.e("dialing-example", "Call failed", activityException);
        }
    }
}
```

Run it and we have a custom dialler on a phone. The code is zipped and provided as an archive along with the *LFY CD*.

Going forward with Android

Just like the dialler, Android supports multiple other APIs including some interesting GIS/GPS to work in cohesion with Google Maps. The modular architecture of Android differentiates the hardware functions and software applications in such a seamless manner that building applications on niche technology areas like GPS, VoIP, etc. is easily achievable by every developer with minimal efforts.

After doing a little bit of Android development, you might be interested in knowing about the award-winning application on Android called "CompareEverywhere" [compare-everywhere.com] written by Jeffrey Sharkey from Montana State University, who won \$250,000 for it. So start building your applications today and who knows, it might be *you* who bags the award the next time. :-)



References

- code.google.com/android
- www.openhandsetalliance.com

By: Roney Banerjee

The author has been in the IT industry for the last nine years and is a passionate Linux follower. He is an entrepreneur, and the co-founder and CTO of Indience InfoSystems.