

```

<!DOCTYPE html>
<html>
<head>
  <meta charset="utf-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <title></title>
  <meta name="description" content="">
  <meta name="viewport" content="width=device-width,
initial-scale=1">
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <div class="header">
    <input class="add-website" type="url"
placeholder="Enter Website e.g: https://www.example.com">
    <button id="add">+</button>
  </div>
  <div class="main">
    <table>
      <tr>
        <th>Websites Blocked</th>
      </tr>
      <tr id="no-website-msg">
        <td>No websites blocked yet.</td>
      </tr>
    </table>
  </div>
  <script src="script.js" defer></script>
</body>
</html>

```

In the above HTML code, we have added the following elements:

- `<input>` - The user will enter the website to be blocked in this input field
- `<button>` - To add and delete websites added to the list
- `<table>` - To display the list of blocked/added websites

To add CSS styles, use the following code:

```

body {
  font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif;
  margin: 0;
  padding: 0;
  box-sizing: border-box;
  display: flex;
  justify-content: center;
  align-items: center;
  flex-direction: column;
}

.add-website {

```

```

  width: 300px;
  padding: 10px;
  margin: 10px;
  border-radius: 4px;
  outline: none;
  border: 1px solid #eee;
}

#add {
  border: none;
  border-radius: 50%;
  background-color: #0081cb;
  color: #ffffff;
  cursor: pointer;
  width: 26px;
  height: 26px;
  cursor: pointer;
}

.delete {
  border: none;
  border-radius: 50%;
  background-color: #e6463b;
  color: #ffffff;
  cursor: pointer;
  width: 26px;
  height: 26px;
  cursor: pointer;
  float: right;
  margin-right: 6px;
  margin-top: 10px;
}

table {
  height: auto;
  width: 388px;
}

table tr th {
  border-bottom: 1px solid #0081cb;
  padding: 5px;
}

table td {
  padding: 8px;
  line-height: 32px;
  width: 100%;
}

table td {
  border-bottom: 1px solid #e2e2e2;
}

```