

```
// To enable the jenkins service at
boot
```

```
sudo systemctl start jenkins
// To start the jenkins
sudo systemctl status jenkins
// To see the current status of
jenkins
```

Adjusting the firewall rules (optional)

If your UFW, i.e., universal firewall, is active, allow the port below to be accessible from the intranet:

```
sudo ufw allow 22
sudo ufw allow 8080
sudo ufw enable
sudo ufw status
```

Open a Web browser and enter `http://IP_Address:8080`. To set up your installation, visit `http://IP_Address:8080`. The Jenkins default port is 8080. You should see the *Unlock Jenkins* screen, which displays the location of the initial password.

Create a new repository

[Import repository](#)

Repository name*

Access level ☒ **This is a private repository**
 Uncheck to make this repository public. Public repositories typically contain open-source code and can be viewed by anyone.

Include a README? Yes, with a tutorial (for begin... ▾

Version control system ☒ **Git** ☐ Mercurial

> [Advanced settings](#)

Create repository Cancel

Figure 1: Creating a Bitbucket repository

Unlocking Jenkins

Open a terminal and enter the following command to get the password. Using that password, you should be able to log in to Jenkins.

```
sudo cat /var/lib/jenkins/secrets/
```

`initialAdminPassword`

Installing suggested plugins or selecting specific plugins for Jenkins

As a beginner, you can go with the 'Install suggested plugins' option. But

Figure 2: Linking Bitbucket with Jira