

```
sudo add-apt-repository ppa:apt-fast/
stable
sudo apt-get update
sudo apt-get install apt-fast
```

Removing language related *ign* from the *apt-get* update

The output of `sudo apt-get` has three kinds of lines — *hit*, *ign* and *get*. *ign* lines are related to language translation. However, if you use all the application packages in English, you do not need a translation of the package database. So if you suppress these language related updates from *apt-get*, the *apt-get* update speed will increase. To do so, open the following file:

```
sudo gedit /etc/apt/apt.
conf.d/00aptitude
```

Then add the following line at the end of this file:

```
Acquire::Languages "none";
```

Tweaking LibreOffice to make it faster

To make LibreOffice faster, open it and go to *Tools* → *Options* and choose *Memory* from the left sidebar. Enable 'Systray Quickstarter' and increase the memory allocation.

Clearing up disk clutter

Try typing `sudo apt-get autoremove` and then `sudo apt-get clean` into a terminal window. The first command removes any unused (redundant) dependencies from the system. The second removes all cached package files. Both are harmless. On a well-used system that's been updated a couple of times, you could free up as much as a gigabyte using these methods (compare the clutter before and after using the `df -h` commands).

Getting a reminder for when you have to leave

If you need a reminder to leave your

terminal, type the following command:

```
leave +hhmm
```

hhmm refers to the time of day in the *hhmm* format, where *hh* is the time in hours (on a 12 or 24 hour clock) and *mm* refers to minutes. All days are converted to a 12-hour clock.

Text formatting

You can reformat each paragraph with the *fmt* command. In this example, I'm going to reformat a file by wrapping overlong lines and filling short lines, as follows:

```
fmt file.txt
```

You can also split long lines, but do not refill; and wrap overlong lines, but do not fill short lines:

```
fmt -s file.txt
```

Enabling firewall

By default, the firewall in Ubuntu is set to allow all incoming connections. So use *ufw* and enable the firewall with the following command (additionally, open port 22 for ssh).

```
sudo ufw enable
```

```
sudo ufw allow 22/tcp
```

Installing non-open source applications

When you first install Ubuntu, use *apt-get* to install 'Ubuntu-restricted-extras'. This installs a list of applications that are not open source and includes Adobe Flashplayer, MS fonts, etc, to name a few. **END** 🐧

By: Harsukhdeep Singh

The author has worked as a QA engineer for the last four years and is an avid open source enthusiast.

PROFIT FROM IOT

Showcasing Latest Tech For IOT Solution Providers



5th Edition

IOTSHOW.IN
13-15 FEB 2020 • KTPO • Bengaluru

AN EVENT FOR
THE **CREATORS** AND
THE **SOLUTION**
PROVIDERS OF IOT

To avoid queues at registration desk, please pre-register

To register, please visit
<https://registration.iotshow.in>

For more information:
• +91-9958881961 • +91-9667743666