

```
name": "Doe", "email": "johndoe@reqres.in"}'
```

In the above command:

- `-X` is used to specify the request type. In this case, it is POST.
- `-H` option is used to specify the HTTP headers.
- `-d` option is used to specify data. In this case, it is JSON payload.

When you execute the above command, it displays the same JSON payload to indicate successful command execution.

2. wget

We often download files from the Internet through a browser or download manager. Wouldn't it be great if we could do the same using the command line interface (CLI)? We can easily do this with the `wget` command, as a non-interactive network download. To download any file, just provide its URL to the `wget` command as follows:

```
$ wget http://softwares.eng.acme.com:8000/ubuntu-18.04.iso
```

We can also download multiple files using this command. To do this, first store all the URLs in a text file as follows:

```
$ cat downloads.txt
http://softwares.eng.acme.com:8000/ubuntu-18.04.iso
http://softwares.eng.acme.com:8000/ubuntu-18.10.iso
http://softwares.eng.acme.com:8000/ubuntu-19.04.iso
http://softwares.eng.acme.com:8000/ubuntu-19.10.iso
```

Now use the `-i` option with the `wget` command:

```
$ wget -i downloads.txt
```

The above command will download all the files one by one in a sequence.

3. lsof

As the name suggests, the `lsof` command is used to list open files. It lists information about the files that are used by various processes. In the Linux world, everything is a file; hence, sockets, directories and pipes are all treated as files. Using this command, we get information about any opened file object.

For example, we can use the `-i` flag to list all the open network connections. Shown below is the sample output of the same:

```
$ lsof -i
COMMAND PID USER FD TYPE DEVICE SIZE/OFF NODE NAME
chrome 7302 jarvis 153u IPv4 276767 0t0 UDP *:mdns
```

```
chrome 7302 jarvis 154u IPv6 276768 0t0 UDP *:mdns
chrome 7302 jarvis 155u IPv4 276769 0t0 UDP *:mdns
chrome 7302 jarvis 156u IPv6 276770 0t0 UDP *:mdns
chrome 7302 jarvis 157u IPv4 276771 0t0 UDP *:mdns
chrome 7302 jarvis 158u IPv6 276772 0t0 UDP *:mdns
chrome 7302 jarvis 174u IPv4 869833 0t0 TCP jarvis-
machine:33736->104.25.57.103:https (ESTABLISHED)
chrome 7302 jarvis 229u IPv4 120340 0t0 TCP jarvis-
machine:57138->stackoverflow.com:https (ESTABLISHED)
chrome 7302 jarvis 252u IPv4 868116 0t0 TCP jarvis-
machine:56792->56.b6.7434.ip4.static.sl-reverse.com:https
(ESTABLISHED)
chrome 7302 jarvis 254u IPv4 276773 0t0 UDP *:mdns
chrome 7302 jarvis 285u IPv4 871409 0t0 TCP jarvis-
machine:36198->104.244.42.136:https (ESTABLISHED)
chrome 7302 jarvis 288u IPv4 868120 0t0 TCP jarvis-
machine:50274->server-13-35-202-12.hyd50.r.cloudfront.
net:https (CLOSE_WAIT)
```

We can also list all the network files in use by a specific process. For instance, the command below shows all the network files used by Chrome.

```
$ lsof -i -a -p 7302
COMMAND PID USER FD TYPE DEVICE SIZE/OFF NODE NAME
chrome 7302 jarvis 153u IPv4 276767 0t0 UDP *:mdns
chrome 7302 jarvis 154u IPv6 276768 0t0 UDP *:mdns
chrome 7302 jarvis 155u IPv4 276769 0t0 UDP *:mdns
chrome 7302 jarvis 156u IPv6 276770 0t0 UDP *:mdns
chrome 7302 jarvis 157u IPv4 276771 0t0 UDP *:mdns
chrome 7302 jarvis 158u IPv6 276772 0t0 UDP *:mdns
chrome 7302 jarvis 174u IPv4 869833 0t0 TCP jarvis-
machine:33736->104.25.57.103:https (ESTABLISHED)
chrome 7302 jarvis 229u IPv4 120340 0t0 TCP jarvis-
machine:57138->stackoverflow.com:https (ESTABLISHED)
chrome 7302 jarvis 252u IPv4 868116 0t0 TCP jarvis-
machine:56792->56.b6.7434.ip4.static.sl-reverse.com:https
(CLOSE_WAIT)
chrome 7302 jarvis 254u IPv4 276773 0t0 UDP *:mdns
chrome 7302 jarvis 285u IPv4 871409 0t0 TCP jarvis-
machine:36198->104.244.42.136:https (ESTABLISHED)
```



Note: Please note that in my case, the process ID of Chrome was '7302'.

We can also list the processes that are listening on a particular port by using the `-i` option with `:'`. For example, the command below lists the processes that are listening on Port 8080:

```
$ lsof -i:8080
```