

```
/** MySQL database password */
define( 'DB_PASSWORD', 'password' );

/** MySQL hostname */
define( 'DB_HOST', 'localhost' );
```

After that, add the following line at the end of the file:

```
//Add below line to install plugins
directly
define( 'FS_METHOD', 'direct' );
```

After modifying these values, save the file and close it.

Section 8 - Setting up the Nginx configuration file

It is time to configure the Web server. You can do so in two ways:

- HTTP only: It will listen on Port 80 only.
- HTTPS and HTTP: In this case, we configure the SSL certificate and listen on both Ports 80 and 443. The request received by Port 80 gets redirected to HTTPS.

The 'HTTP only' method

To configure Nginx for HTTP only, create the configuration files in the `/etc/nginx/sites-available/` directory. You can execute a command to create and open that file:

```
sudo vi /etc/nginx/sites-available/
osfy-test.linuxgeek.in
```

Then copy the following contents to that file.

```
upstream fastcgi_backend {
    server unix:/run/php/php7.4-fpm.
    sock;
}

server {
    listen [::]:80;
    listen 80;
    server_name osfy-test.linuxgeek.
in;

    root /var/www/html/osfy-test.
```

```
linuxgeek.in;
    index index.php;
    access_log /var/log/nginx/osfy-
access.log;
    error_log /var/log/nginx/osfy-
error.log;

    location = /robots.txt {
        allow all;
        log_not_found off;
        access_log off;
    }

    location / {
        try_files $uri $uri/ /index.
php?$query_string;
    }

    location ~ /\. { deny all; }

    location ~ \.php$ {
        try_files $uri =404;
        fastcgi_split_path_info ^(.+\.
php)(/.)$;
        fastcgi_pass fastcgi_backend;
        fastcgi_intercept_errors on;
        fastcgi_index index.php;
        include fastcgi.conf;
    }
}
```

Save this file and exit. After this, execute the following commands:

```
su - // Switch To Root User
ln -s /etc/nginx/sites-available/osfy-
test.linuxgeek.in /etc/nginx/sites-
enabled/
nginx -t //To check whether
configuration is right or not
nginx -s reload //To reload the Nginx
service
```

The HTTP and HTTPS method

To configure Nginx for HTTP and HTTPS, create configuration files in the `/etc/nginx/sites-available/` directory. You can execute a command to create and open that file.

```
sudo vi /etc/nginx/sites-available/
osfy-test.linuxgeek.in
```

Then copy the following contents to that file.

```
upstream fastcgi_backend {
    server unix:/run/php/php7.4-fpm.
    sock;
}

server {
    listen 443 ssl http2;
    server_name osfy-test.linuxgeek.in;

    root /var/www/html/osfy-test.
linuxgeek.in;
    index index.php;
    access_log /var/log/nginx/osfy-
access.log;
    error_log /var/log/nginx/osfy-
error.log;

    location = /robots.txt {
        allow all;
        log_not_found off;
        access_log off;
    }

    location / {
        try_files $uri $uri/ /index.
php?$query_string;
    }

    location ~ /\. { deny all; }

    location ~ \.php$ {
        try_files $uri =404;
        fastcgi_split_path_info ^(.+\.
php)(/.)$;
        fastcgi_pass fastcgi_backend;
        fastcgi_intercept_errors on;
        fastcgi_index index.php;
        fastcgi_param HTTPS on;
        include fastcgi.conf;
    }
}

server {
    listen [::]:80;
    listen 80;
    server_name osfy-test.linuxgeek.in;
    return 301 https://osfy-test.
linuxgeek.in$request_uri;
}
```