

```
[Dheekksha@dheekksha wfuzz-master]$ wfuzz -w wordlist/general/common.txt http://testphp.vulnweb.com/FUZZ
libraries.FileLoader: CRITICAL __load_py_from_file. Filename: /usr/local/lib/python3.7/site-packages/wfuzz/plugins/payloads/shodan.py Exception, msg=No module named 'shodan'
libraries.FileLoader: CRITICAL __load_py_from_file. Filename: /usr/local/lib/python3.7/site-packages/wfuzz/plugins/payloads/bing.py Exception, msg=No module named 'shodan'
*****
* Wfuzz 2.4.5 - The Web Fuzzer
*****

Target: http://testphp.vulnweb.com/FUZZ
Total requests: 949

=====
ID           Response  Lines  Word  Chars  Payload
=====
000000003:   404         7 L    12 W   168 Ch  "01"
000000007:   404         7 L    12 W   168 Ch  "10"
```

Figure 1: Output on fuzzing, part 1

```
0000000946:   404         7 L    12 W   168 Ch  "zap"
0000000947:   404         7 L    12 W   168 Ch  "zip"
0000000948:   404         7 L    12 W   168 Ch  "zipfiles"
0000000949:   404         7 L    12 W   168 Ch  "zips"

Total time: 30.04423
Processed Requests: 949
Filtered Requests: 0
Requests/sec.: 31.58675

[Dheekksha@dheekksha wfuzz-master]$ wfuzz -w wordlist/general/common.txt http://testphp.vulnweb.com/FUZZ
```

Figure 2: Output on fuzzing, part 2

```
[Dheekksha@dheekksha wfuzz-master]$ wfuzz -w wordlist/general/common.txt --hc 404 http://testphp.vulnweb.com/FUZZ
libraries.FileLoader: CRITICAL __load_py_from_file. Filename: /usr/local/lib/python3.7/site-packages/wfuzz/plugins/payloads/shodan.py Exception, msg=No module named 'shodan'
libraries.FileLoader: CRITICAL __load_py_from_file. Filename: /usr/local/lib/python3.7/site-packages/wfuzz/plugins/payloads/bing.py Exception, msg=No module named 'shodan'
*****
* Wfuzz 2.4.5 - The Web Fuzzer
*****

Target: http://testphp.vulnweb.com/FUZZ
Total requests: 949

=====
ID           Response  Lines  Word  Chars  Payload
=====
000000035:   301         7 L    12 W   184 Ch  "admin"
000000162:   403        10 L    29 W   263 Ch  "cgi-bin"
000000229:   301         7 L    12 W   184 Ch  "CVS"
000000412:   301         7 L    12 W   184 Ch  "images"
000000721:   301         7 L    12 W   184 Ch  "secured"

Total time: 48.13123
Processed Requests: 949
Filtered Requests: 944
Requests/sec.: 19.71692
```

Figure 3: Directories

Basic Wfuzz usage includes fuzzing directories, fuzzing Post requests, fuzzing cookies (using *-b* in the command), fuzzing custom headers, HTTP verbs, fuzzing proxies and authentication.

Wfuzz contains a wide range of filter switches to use on payloads. This tool also lets us use previous results and combine the payloads by using iterators.

Fuzzing paths and files

This tool is used to retrieve all the paths

and files with the single command given below:

```
wfuzz -w wordlist/general/common.txt http://testphp.vulnweb.com/FUZZ
```

In Wfuzz, *-w* is used to specify the wordlist used to brute force the directories or files. The file *common.txt* is downloaded along with Wfuzz; if not cloned from GitHub then the wordlist folder can be separately downloaded. It contains all the dictionaries of common lists, one of which can be chosen while launching a brute force attack. The file specified is followed by the target website's URL. The website used here is *vulnweb.com*, which is the test and demonstration site for the Acunetix Web vulnerability scanner. The website's URL, followed by the *fuzz* keyword, will allow for a large number of requests to be processed.

In this case, it is 949 requests. Every word (payload) along with the response number is displayed. The very