

For HTTP POST, the entire form's contents come as a big string, which can be read and parsed in C code, as shown below:

```
int num1,num2,sum;
printf("<!doctype> \
    <html> <body> <form method=\"post\" action=\"\"> \
        <label for=\"fno\">Number1:</label><br> \
        <input type=\"number\" id=\"fno\" name=\"fno\" \
value=%d><br> \
        <label for=\"lno\">Number2:</label><br> \
        <input type=\"number\" id=\"lno\" name=\"lno\" \
value=%d><br><br> \
        <input type=\"submit\" value=\"Submit\"> \
    </form> \
    Sum = %d\
</body> \
</html><br>", num1,num2,sum);
env=getenv("REQUEST_METHOD");
if(strcmp(env, "POST") == 0)
{
    char buffer[200] = {'\0'};
    const char delim[] = "&=";
    char *token;
```

```
int tokenNo=0;
int inputlen = atoi(getenv("CONTENT_LENGTH"));
fread(buffer, inputlen, 1, stdin);
/*parse input fno=4&lno=-2 */
token = strtok(buffer, delim);
while(token!= NULL)
{
    tokenNo++;
    if(2 == tokenNo) num1=atoi(token);
    if(4 == tokenNo) num2=atoi(token);
    token = strtok (NULL, delim);
}
sum = num1+num2;
}
```

You can see that the form is also generated in the code using the `printf` statement.

The entire source code is available at <https://github.com/SupriyoGanguly/tryLighty>. **END** 🐧

By: Supriyo Ganguly

The author is a senior technical officer at Electronics Corporation of India Limited, Hyderabad.



THE COMPLETE MAGAZINE ON OPEN SOURCE



- >> To find dealers to buy copy from news-stand, visit: www.ezine.lfyimag.com
- >> To subscribe, visit: pay.efyindia.com
- >> To buy an ezine edition, visit: www.magzter.com choose Open Source For You