

```
# this is read by the standalone daemon and embedded servers
[server]

# this is only for the mysqld standalone daemon
[mysqld]

#
# * Basic Settings
#
user                = mysql
pid-file            = /var/run/mysqld/mysqld.pid
socket              = /var/run/mysqld/mysqld.sock
port                = 3306
basedir             = /usr
datadir             = /var/lib/mysql
tmpdir              = /tmp
lc-messages-dir     = /usr/share/mysql
skip-external-locking

# Instead of skip-networking the default is now to listen only on
# localhost which is more compatible and is not less secure.
bind-address        = 127.0.0.1

#
# * Fine Tuning
#
key_buffer_size     = 16M
max_allowed_packet  = 16M
thread_stack        = 192K
thread_cache_size   = 8
# This replaces the startup script and checks MyISAM tables if needed
# the first time they are touched
myisam_recover_options = BACKUP
#max_connections    = 100
#table_cache        = 64
#thread_concurrency = 10

#
# * Query Cache Configuration
#
query_cache_limit    = 1M
query_cache_size     = 16M

#
# * Logging and Replication
#
# Both location gets rotated by the cronjob.
```

Figure 4: The MariaDB configuration file

view the configuration file, as shown in Figure 4.

We now need to start the MariaDB server using the following command, as shown in Figure 5.

```
sudo systemctl start mariadb
```

To check if our MariaDB server has started, we use the following command, as shown in Figure 6.

```
sudo systemctl status mariadb
```

You can use the following command to restart the MariaDB server:

```
sudo systemctl restart mariadb
```

Now that we have installed MariaDB, we need to save important data, and keep our database secure. Today, data is very important and valuable, making it all the more important to keep it safe and secure. So, here are the steps that will help you secure your MariaDB database.

First, we set up a password to login into the MariaDB database and set up an authorisation system, using the following command (Figure 7):

```
sudo mysql_secure_installation
```

Once we perform all the prompted actions and steps, our database is now secure and ready to use. Let us do that now.

```
jishnusaurav@jishnusaurav-IdeaPad-L340-15IRH-Gaming:~$ sudo systemctl status mariadb
● mariadb.service - MariaDB 10.1.48 database server
   Loaded: loaded (/lib/systemd/system/mariadb.service; enabled; vendor preset: enabled)
   Active: active (running) since Wed 2021-10-27 00:20:45 IST; 1h 1m ago
     Docs: man:mysqld(8)
           https://mariadb.com/kb/en/library/systemd/
   Process: 1390 ExecStartPost=/bin/sh -c systemctl unset-environment _WSREP_START_POSITION (code=exited, status=0/SUCCESS)
   Process: 1386 ExecStartPost=/etc/mysql/debian-start (code=exited, status=0/SUCCESS)
   Process: 1142 ExecStartPre=/bin/sh -c [ ! -e /usr/bin/galera_recovery ] && VAR=() VAR=$(cd /usr/bin/..; /usr/bin/galera_recovery) [ $? -eq 0 ] && systemctl set-environment _WSREP_START_POSITION=$VAR (code=exited, status=0/SUCCESS)
   Process: 1133 ExecStartPre=/bin/sh -c systemctl unset-environment _WSREP_START_POSITION (code=exited, status=0/SUCCESS)
   Process: 1128 ExecStartPre=/usr/bin/install -m 755 -o mysql -g root -d /var/run/mysqld (code=exited, status=0/SUCCESS)
 Main PID: 1242 (mysqld)
   Status: "Taking your SQL requests now..."
    Tasks: 27 (limit: 4915)
   CGroup: /system.slice/mariadb.service
           └─1242 /usr/sbin/mysqld

Oct 27 00:20:44 jishnusaurav-IdeaPad-L340-15IRH-Gaming systemd[1]: Starting MariaDB 10.1.48 database server...
Oct 27 00:20:44 jishnusaurav-IdeaPad-L340-15IRH-Gaming mysqld[1242]: 2021-10-27 0:20:44 139978850233472 [Note] /usr/sbin/mysqld (mysqld 10.1.48-MariaDB-0ubuntu0.18.04.1) starting as process 1242 ...
Oct 27 00:20:45 jishnusaurav-IdeaPad-L340-15IRH-Gaming /etc/mysql/debian-start[1389]: Upgrading MySQL tables if necessary.
Oct 27 00:20:45 jishnusaurav-IdeaPad-L340-15IRH-Gaming systemd[1]: Started MariaDB 10.1.48 database server.
Oct 27 00:20:45 jishnusaurav-IdeaPad-L340-15IRH-Gaming /etc/mysql/debian-start[1393]: /usr/bin/mysql_upgrade: the '--basedir' option is always ignored
Oct 27 00:20:45 jishnusaurav-IdeaPad-L340-15IRH-Gaming /etc/mysql/debian-start[1393]: Looking for 'mysql' as: /usr/bin/mysql
Oct 27 00:20:45 jishnusaurav-IdeaPad-L340-15IRH-Gaming /etc/mysql/debian-start[1393]: Looking for 'mysqlcheck' as: /usr/bin/mysqlcheck
Oct 27 00:20:45 jishnusaurav-IdeaPad-L340-15IRH-Gaming /etc/mysql/debian-start[1393]: This installation of MySQL is already upgraded to 10.1.48-MariaDB, use --force if you still need to run mysql_upgrade
Oct 27 00:20:45 jishnusaurav-IdeaPad-L340-15IRH-Gaming /etc/mysql/debian-start[1415]: Checking for insecure root accounts.
lines 1-25/25 (END)
```

Figure 5: Starting MariaDB server