

In the above output, you can see the various values in the 'foreign address' column. These are the different IP addresses the local machine is speaking to. We can also find out the process that initiated the above socket connections via the `--program` or `-p` option:

```
> netstat -p | head
```

(Not all processes can be identified; non-owned process info will not be shown, you should have the root access to view all of them.)

Active Internet connections (w/o servers)

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State	PID/Program name
tcp	0	0	arya:40620	51.105.71.137:https	ESTABLISHED	2049/chrome --type=
tcp	0	0	arya:34078	a104-96-204-135.d:https	ESTABLISHED	2049/chrome --type=
tcp	0	0	arya:36442	52.113.206.194:https	ESTABLISHED	2049/chrome --type=
tcp	0	0	arya:36440	52.113.206.194:https	ESTABLISHED	2049/chrome --type=
tcp	0	0	arya:35088	52.114.133.162:https	ESTABLISHED	2049/chrome --type=
tcp	0	0	arya:48510	52.98.59.18:https	ESTABLISHED	2049/chrome --type=
tcp	0	0	arya:44802	1b-140-82-113-26-:https	ESTABLISHED	2049/chrome --type=
tcp	0	0	arya:46554	ec2-65-1-252-10.a:https	ESTABLISHED	2049/chrome --type=

Though a warning is given that not all processes could be identified, the output does seem to have program names in it. The name 'arya' under 'local address' is the host name in this instance. If you wanted to display IPs, you could use `-n` or `--numeric` instead:

```
> netstat -pn | head
```

(Not all processes could be identified, non-owned process info will not be shown, you would have to be root to see it all.)

Active Internet connections (w/o servers)

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State	PID/Program name
tcp	0	0	192.168.3.107:40826			

13.232.113.235:443	ESTABLISHED	2049/chrome --type=
tcp 0 0 192.168.3.107:51168	140.82.112.25:443	ESTABLISHED 2049/chrome --type=
tcp 0 0 192.168.3.107:48510	52.98.59.18:443	ESTABLISHED 2049/chrome --type=
tcp 0 0 192.168.3.107:46554	65.1.252.10:443	ESTABLISHED 2049/chrome --type=
tcp 0 0 192.168.3.107:35838	13.107.6.171:443	ESTABLISHED 2049/chrome --type=
tcp 0 0 192.168.3.107:60932	52.114.40.56:443	ESTABLISHED 2049/chrome --type=
tcp 0 0 192.168.3.107:35130		
13.126.138.201:443	ESTABLISHED	2049/chrome --type=
tcp 0 0 192.168.3.107:45854		
52.114.159.213:443	ESTABLISHED	2049/chrome --type=

In this case, it can be confirmed that the local IP address is 192.168.3.107.

```
> ip a show eno1
```

```
2: eno1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 94:c6:91:a6:33:df brd ff:ff:ff:ff:ff:ff
    altname enp0s31f6
    inet 192.168.3.107/24 brd 192.168.3.255 scope global dynamic noprefixroute eno1
        valid_lft 69032sec preferred_lft 58232sec
    inet6 fe80::96c6:91ff:fea6:33df/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
    inet6 fe80::4ed1:9a96:4747:eb59/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
```

One of my favourite use cases for using netstat is to see which of the ports from my machine are being exposed locally to my LAN or the Internet. You can use `-l` to just list the listening sockets and couple it with `-t` to filter the TCP protocol.

```
> netstat -nlt --program
```

(Not all processes could be identified, non-owned process info will not be shown, you would have to be root to see it all.)

Active Internet connections (only servers)

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State	PID/Program name
tcp	0	0	0.0.0.0:22	0.0.0.0:*	LISTEN	-
tcp6	0	0	:::22	:::*	LISTEN	-

As in this case we are unable to see the program name, we