

```
[11] "commonmark" "crayon" "cubature" "DBI"
"desc"
[16] "diffobj" "digest" "ellipsis" "evaluate"
"fansi"
[21] "fastmap" "fontawesome" "fs" "glue"
"highr"
[26] "htmltools" "httpuv" "IRdisplay" "IRkernel"
"jquerylib"
[31] "jsonlite" "knitr" "kyotil" "later"
"lifecycle"
[36] "magrittr" "memoise" "mime" "mvtnorm"
"pbdZMQ"
[41] "pillar" "pkgconfig" "pkgload" "plogr"
"praise"
[46] "processx" "promises" "ps" "R6" "rappdirs"
[51] "Rcpp" "rematch2" "repr" "rjson" "rlang"
[56] "rmarkdown" "rprojroot" "RSQLite" "rstudioapi"
"RUnit"
[61] "sass" "shiny" "sourcetools" "stringi"
"stringr"
[66] "testthat" "tibble" "tinytest" "tinytex"
"utf8"
[71] "uuid" "vctrs" "waldo" "withr"
"xfun"
[76] "xtable" "yaml" "base" "boot" "class"
[81] "cluster" "codetools" "compiler" "datasets"
"foreign"
[86] "graphics" "grDevices" "grid" "KernSmooth"
"lattice"
[91] "MASS" "Matrix" "methods" "mgcv" "nlme"
[96] "nnet" "parallel" "rpart" "spatial"
"splines"
[101] "stats" "stats4" "survival" "tcltk" "tools"
[106] "utils"
```

The `library()` function will open a new window showing a list of available packages along with a one-line description of the package, as illustrated below:

```
> library()
Packages in library '/home/guest/R/x86_64-pc-linux-gnu-library/4.1':
AMR                Antimicrobial Resistance Data
Analysis
base64enc          Tools for base64 encoding
bit                Classes and Methods for Fast
Memory-Efficient
                   Boolean Selections
bit64              A S3 Class for Vectors of 64bit
Integers
blob               A Simple S3 Class for Representing
```

```
Vectors of
                   Binary Data ('BLOBS')
brio               Basic R Input Output
bslib              Custom 'Bootstrap' 'Sass' Themes for
'shiny'
                   and 'rmarkdown'
cachem             Cache R Objects with Automatic
Pruning
callr              Call R from R
cli                Helpers for Developing Command Line
Interfaces
commonmark         High Performance CommonMark and
Github Markdown
                   Rendering in R
crayon             Colored Terminal Output
cubature           Adaptive Multivariate Integration
over
                   Hypercubes
DBI                R Database Interface
desc              Manipulate DESCRIPTION Files
diffobj            Diffs for R Objects
digest             Create Compact Hash Digests of R
Objects
ellipsis           Tools for Working with ...
evaluate           Parsing and Evaluation Tools that
Provide More
                   Details than the Default
fansi              ANSI Control Sequence Aware String
Functions
fastmap            Fast Data Structures
fontawesome        Easily Work with 'Font Awesome'
Icons
fs                 Cross-Platform File System
Operations Based on
'libuv'
...
```

You can install multiple packages with the `install.packages` function passing it a vector of package names. For example, the 'abc' package provides tools for approximate Bayesian computation (ABC), and the 'abtest' tool implements Bayesian A/B testing. You can install both using the following command:

```
> install.packages(c("abc", "abtest"))
```

You can now verify that the *installed packages* are listed from the *available.packages* function, as shown below:

```
> (.packages(all.available=TRUE))
```