

```

metadata:
  name: mysecret
  namespace: addon-system
type: Opaque
data:
  username: c2liaQ==
  password: bXlZZWNyZXQ=

```

Both `c2liaQ==` and `bXlZZWNyZXQ=` are base64 encoded values of the secrets:

```
> echo -n c2liaQ== | base64 -d
sibi
```

We want to convert these to Sealed Secrets type so that they can be stored in a public place. Make sure you have the kubeseal executable in your `$PATH`. You can create a Sealed Secrets manifest like this:

```

> kubeseal -o yaml < secret.yaml
apiVersion: bitnami.com/v1alpha1
kind: SealedSecret
metadata:
  creationTimestamp: null
  name: mysecret
  namespace: addon-system
spec:
  encryptedData:

    password: AgBjKaKjdpXf080pwICUKkbHMOt0p/29miuKEgMzTJsm
SQFE4mAgX5S/RAjQY0hwXKQoa1VhbWou3S379xy+BiUVZsSeFub8gl TN
Dx6RP01UUYo+R2k08qGT1ULqiB39+/INS1u68R18Q2MzlnP+anHdCds
0tWms51 aSbuBDXvkws6TGfxjTmttgCeYBOSfsZ33rsgDCesPAXxsSf2y
WcdofAWvDIh5QH5HDIveZ8qsL3mPVq9JpDrwvxdArLqPARu3uV8GHVA 5da
H9192vhEbsEQZmayz/4l8128AwZ8ZuUmIKH/SIwHzqbM0nb+2yxCqRw bBR
cpq7pd4ygJ+Zph9P4tyl+YQ9YBgHBqUQHrISZLrJURbdcTAZlUr WIG0en
VcEsXOUj9AscjveE4sy+PDgs0dm5T00/wfUinAqV5Ncc1Swc1YvrVqn6A0
J6sSeHdA3zblYtQzhL90wfPj1n0yWtVrhngqh+8SH0DJnrrBBf 0h73qg1
FXJmAK46qx P5ZQCUCQ0CxxPj7S1RYPk5QjakOMT0kh36UxZ0nwqQ G8c7
V5RVUNvbkuVwi9Lp8ilPSKBHAYt9agoB/+iJzI64jbMGMqd7pL10PmZ2
FsI2yaLAlrkYJy03sibiF3VgA5v80x10eTa2ux9VjaedkMSHIbcT0ewDW
kXzc5iY3qH7bMM0AvLZLDjy1DCayzk/iYOWRZD3Cgw==
username:
AgAq/gkw04XAViAuNGNnApJKQIGzn9V4yf1ziLj+/vXtCu37bj27nei46RS
1n5SZ/1AC1YM2LLYScw+ZB7oZDK2bXNFGYxv9XgA6t0 3+vgnN1v7VxrDDI
kpUeAizddfrmfUzL2a18Erm3DZzCiGio6ZLrVfg52trh tMeKZqqamewkQ0n
ZkTPNGKgwAu2X8RTSD2CbQrWm3DjQ4z9gwxQ19gTraMJl 3xcMs7BynI
fliE5yuERls1VLDQgD+ZHwvP5V1aD1g3H20is4iAhP0QZzy0dNf/Lc11y
FmrwZHL2trIGtedBtl1QBo6PkYsqNrbEQheMoiAn+djR2i191LS1Nw6
9N4w4VMGw8VDcBoXXwd17iczYjhcN9G4q4b0Pj7Mw6mcpmdirGMYXSbDk0JGuI
FwJeXvL/q1000COYp8PR2c/fimQ198WpUrfAa+jkqzw0StJY1/tmdISNIquif7
ji0bspi8ujuNB1/5FgHcxPLw7sZBRXINY83CqitNv+NOW+8qt

```

```

gAAX1jyNPEAj/25tPbFaNbmI+f+x/nAMG3Xwbl4a9QFPkdUqnGrIYPxAlIEQ/
mNdmzbQYAS7ZFq2CU/iYPH5Jh4iNCxdZ+AS9EQG9L/oVXGnq3NsVCzT35C
SORD+tFo55D5ebzi+Ui0fy/Gl3n/QiJJZ2V3YxdnxbQsf73KR4VGM0bf24Nr
iIBf0x+a
template:
  data: null
  metadata:
    creationTimestamp: null
    name: mysecret
    namespace: addon-system
  type: Opaque

```

Now you can have the above `yaml` file as part of your repository and even share it publicly without worrying about any leak. Let us save this `yaml` file as `sealed-secret.yaml` and apply the above manifest:

```
> kubectl apply -f sealed-secret.yaml
sealedsecret.bitnami.com/mysecret created
```

You can observe that your secret will get populated by the controller in a couple of seconds:

```
> kubectl get secrets -n addon-system | rg mysecret
```

NAME	TYPE	DATA	AGE
mysecret	Opaque	2	69s

You can even check the kubeseal controller logs to verify that it unsealed your secret:

```
> kubectl -n kube-system logs -f pods/sealed-secrets-
controller-78476684bf-jfbpsp
...
2021/12/03 14:44:13 Updating addon-system/mysecret
```

Let's verify that our secrets are indeed what we stored:

```
> kubectl -n addon-system get secret mysecret -o=jsonpath={.
data}
{"password":"bXlZZWNyZXQ=","username":"c2liaQ=="}
```

And that confirms that the unsealing did happen properly!

You can also save the certificate offline and generate Sealed Secrets without having access to the controller. Let's fetch the certificate:

```
> kubeseal --fetch-cert
```

The output will give the complete certificate, which can be stored locally:

```
> kubeseal --fetch-cert > sealed-secrets.pem
```