

```
[1] "3.36.0"

$dbname
[1] "/home/guest/Chinook_Sqlite.sqlite"

$username
[1] NA

$host
[1] NA

$port
[1] NA
```

The class of the driver and connection objects can be displayed using the `class()` function.

```
> class(driver)
[1] "SQLiteDriver"
attr(,"package")
[1] "RSQLite"

> class(connection)
[1] "SQLiteConnection"
attr(,"package")
[1] "RSQLite"
```

A number of tables exist in the example Chinook database, as shown below:

```
$ sqlite3 Chinook_Sqlite.sqlite
SQLite version 3.36.0 2021-06-18 18:36:39
Enter ".help" for usage hints.
```

```
sqlite> .tables
Album      Employee   InvoiceLine PlaylistTrack
Artist     Genre      MediaType  Track
Customer   Invoice     Playlist
```

You can also list the available tables from R using the `dbListTables()` function as follows:

```
> dbListTables(connection)
[1] "Album"      "Artist"     "Customer"
"Employee"
[5] "Genre"      "Invoice"    "InvoiceLine"
"MediaType"
[9] "Playlist"   "PlaylistTrack" "Track"
```

The `dbGetQuery()` function takes the connection object as an argument and the actual query to execute on the database, as shown in Figure 3.

```
> dbGetQuery(connection, "select * from Genre")
  GenreId      Name
1       1      Rock
2       2      Jazz
3       3      Metal
4       4 Alternative & Punk
5       5      Rock And Roll
6       6      Blues
7       7      Latin
8       8      Reggae
9       9      Pop
10      10      Soundtrack
11      11      Bossa Nova
12      12      Easy Listening
13      13      Heavy Metal
14      14      R&B/Soul
15      15      Electronica/Dance
16      16      World
17      17      Hip Hop/Rap
18      18      Science Fiction
19      19      TV Shows
20      20      Sci Fi & Fantasy
21      21      Drama
22      22      Comedy
23      23      Alternative
24      24      Classical
```

Figure 3: `dbGetQuery()`

Finally, you can close the database connection, unload the database driver and free memory using the `dbDisconnect()` and `dbUnloadDriver()` methods:

```
> dbDisconnect(connection)
> dbUnloadDriver(driver)
```

You are encouraged to try the above R libraries on your CSV, JSON files and databases, read the references, and the respective R library documentation for more information. 

References

- [1] [Moro et al., 2014] S. Moro, P. Cortez and P. Rita; A Data-Driven Approach to Predict the Success of Bank Telemarketing. Decision Support Systems, Elsevier, 62:22-31, June 2014
- [2] Rawassizadeh, R., Tomitsch, M., Wac, K., & Tjoa, A. M. (2013). UbiqLog: a generic mobile phone-based life-log framework. Personal and ubiquitous computing, 17(4), 621-637.
- [3] Rawassizadeh, R., Momeni, E., Dobbins, C., Mirza-Babaei, P., & Rahnamoun, R. (2015). Lesson Learned from Collecting Quantified Self Information via Mobile and Wearable Devices. Journal of Sensor and Actuator Networks, 4(4), 315-335.
- [4] Example Colors JSON File, <https://www.sitepoint.com/colors-json-example/>
- [5] Chinook Database, <https://github.com/lerocha/chinook-database>
- [6] RSQLite, <https://rsqlite.r-dbi.org/index.html>

 By: **Shakthi Kannan**

The author is a Free Software enthusiast.