

R Series: The Syntax

In this second article in the series on 'R, Statistics and Machine Learning', we are going to learn the syntax of the R programming language. We will use R version 4.1.0 installed on Parabola GNU/Linux-libre (x86-64). The syntax for constants will be discussed first, followed by operators, functions, expressions and, finally, control structures. The Tidyverse R style guide, based on Google's R style guide with a few changes, will also be addressed.



Numbers are represented in R as is and a few examples are given below:

```
$ R
R version 4.1.0 (2021-05-18) -- "Camp Pontanezen"
Copyright (C) 2021 The R Foundation for Statistical Computing
Platform: x86_64-pc-linux-gnu (64-bit)

R is free software and comes with ABSOLUTELY NO WARRANTY.
You are welcome to redistribute it under certain conditions.
Type 'license()' or 'licence()' for distribution details.

Natural language support but running in an English locale

R is a collaborative project with many contributors.
Type 'contributors()' for more information and
'citation()' on how to cite R or R packages in publications.

Type 'demo()' for some demos, 'help()' for on-line help, or
'help.start()' for an HTML browser interface to help.
Type 'q()' to quit R.
```

```
> 3.1415
[1] 3.1415

> 5
[1] 5

> 0x00FF
[1] 255

> 2^10
[1] 1024

> +1i
[1] 0+1i

> "Foo"
[1] "Foo"

> 'Foo'
```

Text can be enclosed within a pair of quotes (single or double), as shown below: