



## Split larger files using 7zip

```
# 7z a -v200m -mx0 ubuntu.7z /test/ubuntu.iso
```

The command given above will create 200MB sized files from the ubuntu.iso. The -v200m is the volume size (use k for kilobytes and g for gigabytes); and the -mx0 switch tells 7-Zip not to use compression, that is, to just split data into parts.

To extract a file, just type:

```
# 7z x ubuntu.7z.001
```

...or type:

```
# 7z e ubuntu.7z.001
```



**Note:** You need to install 7zip if it's not already installed.

To install it on Ubuntu, run the following command:

```
$ sudo apt-get install p7zip-full
```

—Shiju V,

shijusvk@gmail.com



## Setting up routes with ipv6

Add the ipv6 route using the 'ip' command, as follows:

```
#ip -6 route add <ipv6network>/<prefixlength> via <ipv6address>
```

```
#ip -6 route add 2000::/3 via 2001:0db8:0:f01::1
```

Add the ipv6 route using 'route':

```
#route -A inet6 add <ipv6network>/<prefixlength> gw <ipv6address> [dev <device>]
```

```
#route -A inet6 add 2000::/3 gw 2001:0db8:0:f01::1
```

—Shreehari Dhat,

shreeharidhat@gmail.com



## Formatted output with the column command

The *column* utility formats its input into multiple columns. We can use this command to view the formatted output of the *mount* command:

```
[bash]$ mount | column -t
```

The output is:

```
/dev/sda6 on / type ext4
(rw,errors=remount-ro)
proc on /proc type proc
(rw,noexec,nosuid,nodev)
sysfs on /sys type sysfs
(rw,noexec,nosuid,nodev)
...
...
/dev/sda7 on /home type ext4
(rw)
systemd on /sys/fs/cgroup/systemd type cgroup
(rw,noexec,nosuid,nodev,none,name=systemd)
gvfsd-fuse on /run/user/1000/gvfs type fuse.
gvfsd-fuse (rw,nosuid,nodev,user=naru)
```

—Narendra Kangralkar,

narendrakangralkar@gmail.com



## Find listening network ports

With the help of the following command, you can find the processes that are running and their associated port numbers. This command can help systems administrators troubleshoot various production issues (like when a process is killed and the port number related to the service is still in use). With this command, it's easy to trace the port number and its associated processes.

```
# netstat -tulpn
```

Active Internet connections (only servers)

| Proto   | Recv-Q | Send-Q           | Local Address  | Foreign   |
|---------|--------|------------------|----------------|-----------|
| Address | State  | PID/Program name |                |           |
| tcp     | 0      | 0                | 127.0.0.1:3306 | 0.0.0.0:* |
| LISTEN  | 1138   |                  | /mysqld        |           |
| tcp     | 0      | 0                | 0.0.0.0:111    | 0.0.0.0:* |
| LISTEN  | 858    |                  | /portmap       |           |
| tcp     | 0      | 0                | 0.0.0.0:80     | 0.0.0.0:* |
| LISTEN  | 1607   |                  | /apache2       |           |
| tcp     | 0      | 0                | 0.0.0.0:55991  | 0.0.0.0:* |
| LISTEN  | 918    |                  | /rpc.statd     |           |

—Munish Kumar,

munishtotech@gmail.com

END

## Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at [www.opensourceforu.com](http://www.opensourceforu.com). The sender of each published tip will get a T-shirt.