

```
<script type="text/javascript">
$(document).ready(function() {
  $('.carousel').carousel({interval: 4000});
});
</script>
```

Apart from this, the carousel plugin also offers several options like intervals, pauses and wraps to showcase your content, which makes the Web page even more dynamic, in terms of features.

Closing with the footer

The last section in our Web page, the footer, is going to contain *Help* and *Terms and Conditions*, with text aligned to the centre and the right side:

```
<footer class="footer">
<div class="span4 text-center">
<p> <a href="#">Help</a> &nbsp; <a href="#"> Terms & Conditions</a>
&nbsp; &nbsp; &copy; Leisurely Getaways 2014</p>
</div></footer>
<div class="span4 text-right">
```

Continued from page ...36

```
, connectPassword = "postgres123"
, connectDatabase = "test"
}
result <- try (execute conn "insert into social.users (id,
fname, lname) values (?, ?, ?)" ["4" :: String, "Laurel" ::
String]) :: IO (Either SomeException Int64)
case result of
  Left ex -> putStrLn $ "Caught exception: " ++ show ex
  Right val -> putStrLn $ "The answer was: " ++ show val
close conn
```

The error is observed when the main function is executed as shown below:

```
ghci> main
Caught exception: FormatError {fmtMessage = "3 '?' characters,
but 2 parameters", fmtQuery = "insert into social.users (id,
fname, lname) values (?, ?, ?)", fmtParams = ["4","Laurel"]}
```

You can also retrieve multiple records from the database and use the results, with the help of a *map* function. An example is illustrated below:

```
{-# LANGUAGE OverloadedStrings #-}
```

```
import Database.PostgreSQL.Simple
import Control.Monad
import Data.Text as Text
```

```
<p> Powered by Twitter Bootstrap 3.3.2</p></div>
```

You can download the entire source code of this Web page from https://github.com/VinayPatkar/Tourist_Bootstrap.git. It contains *custom.css* and *index.html* files.

As we are done creating a basic Web page using Bootstrap, it's time to now dive deeper into it and explore its more advanced features. For more learning, refer to the links given under 'References'. 

References

- [1] <http://getbootstrap.com/examples/carousel/>
- [2] <http://getbootstrap.com/components/#dropdowns>
- [3] <https://wrapbootstrap.com/>

By: Shubhra Rana and Vinay Patkar

Shubhra Rana is a software development engineer at Dell R&D, Bengaluru, and is interested in network security and cryptography.

Vinay Patkar works as a software development engineer at Dell India R&D Centre, Bengaluru, and has close to two years' experience in automation and Windows Server OS. He is interested in virtualisation and cloud computing technologies.

```
main :: IO ()
main = do
  conn <- connect defaultConnectInfo
  { connectUser = "postgres"
  , connectPassword = "postgres123"
  , connectDatabase = "test"
  }
  users <- query_ conn "SELECT fname, lname FROM social.users"
  forM_ users $ \(fname, lname) ->
    putStrLn $ Text.unpack fname ++ " " ++ Text.unpack lname
  close conn
```

The output after executing the above code in GHCi returns the actual data:

```
ghci> main
Edwin Brady
Ulf Norell
Simon Peyton Jones
```

Please refer to the *Database.PostgreSQL.Simple* documentation for more examples and usage at <https://hackage.haskell.org/package/postgresql-simple-0.4.10>. 

By: Shakthi Kannan

The author is a free software enthusiast and blogs at shakthimaan.com