

Table 1: HTML5/JavaScript features

Function	Technology	Features
Audio	Web audio API	API for processing and synthesising audio.
Graphics	WebGL (OpenGL ES 2.0)	API for rendering 3D and 2D images. Compatible with browsers supported by plugins. Note: Not supported on mobiles but can use OpenGL wrappers
Input	Touch events, gamepad API, device sensors, WebRTC, full screen API, pointer lock API	WebRTC – Getusermedia can get hardware access
Language	JavaScript (or C/C++ using Emscripten to compile to JavaScript)	JavaScript has support for lots of game engines/frameworks
Networking	WebRTC and/or WebSockets	Allows interactive sessions between user's browser and server
Storage	IndexedDB	Client side storage for data
Web	HTML, CSS, SVG, social API	Types of APIs and languages for development

Source: Mozilla Development Network and HTML5 Forum

```

<style>
#stageCanvas
{
    background-color:#333333;
}
</style>
<!-- import the Easel library. Downloaded from:
    http://easeljs.com/ -->
<script src="scripts/easel.js"></script>
<script>
//EaselJS Stage instance that wraps the Canvas
element
var stage;
var circle;

//radius of the circle Graphics that we will draw.
var CIRCLE_RADIUS = 10;
var circleXReset;
var bounds;

//initialize function, called when page loads.
function init()
{
    //check and see if the canvas element is
supported in
    //the current browser
    if(!!!document.createElement('canvas').getContext())
    {
        var wrapper = document.getElementById("canvasWrapper");
        wrapper.innerHTML = "Your browser does not
appear to support" + "the HTML5 Canvas element";
        return;
    }

    //get a reference to the canvas element
    var canvas = document.

getElementById("stageCanvas");

//copy the canvas bounds to the bounds instance.
bounds = new Rectangle();
bounds.width = canvas.width;
bounds.height = canvas.height;

//pass the canvas element to the EaselJS Stage instance
stage = new Stage(canvas);

//Create an EaselJS Graphics element to create the
//commands to draw a circle
var g = new Graphics();

//stroke of 1 px
g.setStrokeStyle(1);

//Set the stroke color, using the EaselJS
g.beginStroke(Graphics.getRGB(255,255,255,.7));

//draw the circle
g.drawCircle(0,0, CIRCLE_RADIUS);

circle = new Shape(g);

//set the initial x position, and the reset position
circle.x = circleXReset = -CIRCLE_RADIUS;

//set the y position
circle.y = canvas.height / 2;

//add the circle to the stage.
stage.addChild(circle);

//tell the stage to render to the canvas
stage.update();

```

Continued on page... 46