

```
[~] ./f4.txt
[~] ./f1.txt
[~] ./f10.txt
[~] ./f7.txt
```

In the output, the '+' sign before the file name means the file has been preserved and the '-' sign means the file has been deleted.

—Narendra Kangralkar,
narendrakangralkar@gmail.com



Change the Linux terminal name using the command line

To change the name of the terminal to the hostname, execute the following command:

```
echo -ne '\033]0;${bin/hostname}'\007'
```

If you want to change the terminal name to anything else, change it to what's shown below:

```
echo -ne '\033]0;nameofterminal'\007'
```

You can change the terminal of Server B; when you ssh from Server A to Server B, you can add the following script...

```
echo -ne '\033]0;${bin/hostname}'\007'
```

...in the `.bashrc` under the home directory of the user.

—Paul Jany, pauljanygodwin@gmail.com



The ESpeak text-to-speech converter

Many people don't know about ESpeak. It is a text-to-speech converter with which you can write some text, and these lines will be read out loud.

Consider the following examples to get a better understanding of it.

```
# espeak --stdout | aplay
```

The above command will take the words interactively from the standard input and convert it to speech.

```
# espeak --stdout -t mydoc.txt | aplay
```

The above command will convert the text from `mydoc.txt` to speech.

```
# espeak -t mydoc.txt -w myaudio.wav
```

You can even have audio for different languages, as shown above.

There is an option to increase or decrease the number of spoken words per minute. You can specify the number of words using the `-s` switch. The default is 160 words per minute. In the example below, we have reduced it to 140 words per minute.

```
# espeak -s 140 -f mydoc.txt | aplay
```

The following example will use 'en-uk' – British English – to translate the text to speech.

```
# espeak -v en-uk --stdout 'I will get EFY T Shirt' | aplay
```

—Mohammad Azimuddin,
azim.chisty@gmail.com



Start programs or scripts at system bootup

The script `/etc/rc.local` is to be used by the systems administrator. It is executed after all the normal system services have been started. Administrators can use it to get the summary of the server (like memory status, hardware status, and others). The reports can be sent to a personal mail ID. The following is an entry inside the `/etc/rc.local` file:

```
#vi /etc/rc.local
```

```
'echo last' | /bin/mailx -s "Last logged-in  
users in system " user@gmail.com
```

Save the file by pressing `!wq!`

Next time, when the server boots, a mail will be thrown with the report of the last logged-in user's information — the same way programs or scripts can be placed inside `/etc/rc.local`, as shown below.

Here's a program example:

```
/opt/tivoli/tsm/client/ba/bin/dsmc sched > /dev/null 2>&1 &
```

This is used to start the TSM (Tivoli storage manager) client to run a backup.

—ManuPrasad Mukundan,
mmanuprasad@gmail.com

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.