

Table 1

| Jade           | HTML expansion                                                                                                                   |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| doctype        | <!DOCTYPE html>                                                                                                                  |
| doctype mobile | <!DOCTYPE html PUBLIC "-//WAP-FORUM/DTD XHTML Mobile 1.2//EN" "http://www.openmobilealliance.org/tech/DTD/xhtml-mobile-1.2.dtd"> |
| doctype xml    | <?xml version="1.0" encoding="utf-8"?>                                                                                           |

For more doctypes, refer to online documentation (see References).

## More HTML elements

The example given in Figure 2 has more HTML elements than a simple 'Hello world' program.

## Variables and iterators

A templating language cannot be complete without variables and control structures. Given below is an example of a common page that can generate two different HTML pages — one for Bollywood actors and another for the movies. You could also generate one page combining actors and their movies.

```
- var page = {'title': 'Bollywood', 'heading': 'Bollywood
Home'};
- var actors = ['Shah Rukh', 'Aamir', 'Kareena', 'Kangana'];
- var movies = ['Ra.One', '3 Idiots', 'Jab We Met', 'Queen'];
- var about = 'movies';
- var list = ((about == 'actors')? actors:movies);
doctype html
html
  title #{page.title}

  body
    h1 #{page.heading}
    p This page is all about #{about}.
    h2 All our #{about}
    ul
      li #{list[0]}
      li #{list[1]}
      li #{list[2]}
      li #{list[3]}
    footer &copy; Copyright 2015 Janardan Revuru
```

Snippet 2: An example with variables, lists and ternary operator

The given example is self-explanatory. Here are a few key points to note. Line 5 has the ternary operator used to switch between pages — Actors or Movies. Variable substitution happens with `#{variable}`.

## Iterators

In Snippet 2, lines 15 to 18 can be replaced by the iterator




Figure 2: An example with more HTML elements

feature of Jade. This eliminates repetition of list item tags equal to the number of list elements. Jade also has a 'while' iterator for conditional looping.

```
each val in list
  li= val
```

## Jade command line options

In Snippet 2, we have variables `page.title`, `page.header` and `about` inside the file. We can also pass them as command line parameters. With this, you can generate different pages with different content.

From Snippet 2, remove lines 1 and 4 where we declare variables. From the command line, pass it as an object. Jade also takes a JSON file name, which contains an object instead of a JSON string.

```
$ jade -P -O '{"page": {"title": "Bollywood", "heading": "Bollywood Home"}, "about": "actors"}' var.jade
```

## Bollywood's Home

This page is about movies.

### All our movies

- Ra.One
- 3 Idiots
- Jab We Met
- Queen

Copyright 2015 Janardan Revuru

Figure 3: The output of Snippet 2

Other important command line options are:

```
-P --pretty           compile pretty html output
-p --path <path>     filename used to resolve includes
-O --obj <path>|str  JavaScript options object or JSON
                      file containing it
```