

the router is matched.

The code below shows a sample route with a literal route.

```
'router' => array(
    'routes' => array(
        'home' => array(
            'type' => 'Zend\Mvc\Router\Http\Literal',
            'options' => array(
                'route' => '/',
                'defaults' => array(
                    'controller' => 'Application\Controller\Index',
                    'action' => 'index',
                ),
            ),
        ),
    ),
)
```

- 2. Segment:** This matches a segment of the router. It is specified using a colon and alphanumeric characters. In the code below, *userId* is the segment parameter that must be present in the requested URI. So, the URL will be *http://yourdomain.com/user/edit/5*, where 5 is the user ID that we want to edit. These types of routers have option parameters named *constraints*, which consist of validation using the regex of each segment. In this example, *userId* should be an integer.

```
'router' => array(
    'routes' => array(
        'user-edit' => array(
            'type' => 'Zend\Mvc\Router\Http\Segment',
            'options' => array(
                'route' => '/user/edit/:userId',
                'constraints' => array(
                    'userId' => '[0-9]+',
                ),
                'defaults' => array(
                    'controller' => 'Application\Controller\User',
                    'action' => 'index',
                ),
            ),
        ),
    ),
)
```

The optional segment is surrounded by brackets. For example, *pageId* is optional in the listing page.

```
'route' => 'users/list[:pageId]'
```

- 3. Hostname:** This router is used to match the requested

hostname. It returns matched router data if the hostname is matched. As shown in code below, only *http://admin.todo-local.com* will be able to access this action page.

```
'router' => array(
    'routes' => array(
        'home' => array(
            'type' => 'Zend\Mvc\Router\Http\Hostname',
            'options' => array(
                'route' => 'admin.todo-local.com',
                'defaults' => array(
                    'controller' => 'Application\Controller\Admin',
                    'action' => 'index',
                ),
            ),
        ),
    ),
)
```

- 4. Regex:** You can match the request URI by using the regex router also. As shown in the host router code, the route is defined in the regex route configuration. You need to specify *spec*, which is used while assembling the URI from the router. This route will match URLs like *http://todo-local.com/blog/11.html*.

```
# Host router
'router' => array(
    'routes' => array(
        'home' => array(
            'type' => 'Zend\Mvc\Router\Http\Regex',
            'options' => array(
                'regex' => '/blog/(?<blogId>[0-9]+).html',
                'spec' => '/blog/%blogId%',
                'defaults' => array(
                    'controller' => 'Application\Controller\Blog',
                    'action' => 'index',
                ),
                'format' => 'html',
            ),
        ),
    ),
)
```

- 5. Method:** This router checks for valid requested methods in the requested URI.

```
'router' => array(
    'routes' => array(
        'method-route' => array(
            'type' => 'Literal',
            'options' => array(
```