



Figure 1: Structure of the JQuery page



Figure 2: A simple form with the 'Select' option and 'Submit' button

Figure 1 shows the structure of the JQuery page.

Events and methods

The JQuery Mobile framework that extends the JQuery core is available using *\$.mobile*, which also provides access to JQuery Mobile-specific events and methods. Some of these, which are exposed with *\$.mobile*, are described below.

We need to bind events to JQuery Mobile by using *Live()* and *Bind()* methods like touch events including tap, tap-hold and various swipe and virtual mouse events. We can also bind to orientation changes and scroll events such as *scrollstart* and *scrollstop*.

One more page event allows us to receive notifications:

- Prior to a page's creation
- When a page is created
- Just before the page is shown or hidden
- When the page is shown or hidden

JQuery Mobile provides many methods with the *\$.mobile* object, such as:

1. *\$.mobile.changePage*: This is used to programmatically change one page to another.

Example: If we need to go to the page *weblog.php* using a slide transaction, then we will use the following command:

```
$.mobile.changePage("weblog.php", "slide");
```

2. *\$.mobile.loadPage*: This is used to load an external page, enhance it with JQuery Mobile and insert it into the DOM.
3. *\$.mobile.showPageLoadingMsg*: This is used to show a page loading message.
4. *\$.mobile.hidePageLoadingMsg*: This hides the page loading message.
5. *\$.mobile.path.isSameDomain*: This is a utility method that is used to compare the domain of two URLs.
6. *\$.mobile.activePage*: This is used to get a reference to the page that is currently being viewed.

Forms

Forms are a common Web artifact for posting information

to a server that JQuery Mobile supports. There are many form UI components like text inputs, search inputs, sliders, flip toggle switches, radio buttons, check boxes, select menus and theming forms. They can all be created easily. JQuery Mobile provides a rich set of form elements.

Shown below is the code for a form that has a 'Submit' button:

```
<form action="forms-results.php" method="get">
  <fieldset>
    <div data-role="fieldcontain">
      <label for="select-options" class="select">Choose an
option:</label>
      <select name="select-options" id="select-options">
        <option value="option1">Option 1</option>
        <option value="option2">Option 2</option>
        <option value="option2">Option 3</option>
      </select>
    </div>
    <button type="submit">Submit</button>
  </fieldset>
</form>
```

The result of the code is shown in Figure 2.

Page transitions

JQuery Mobile provides support for CSS based page transitions, which are applied when navigating to a new page and back. The transitions include:

1. *Slide*: This transition provides a horizontal transition.
2. *Slideup* and *Slidedown*: These provide transitions up and down the screen.
3. *Pop*: This provides an 'explosion' type of transition.
4. *Fade*: This provides a fading transition.
5. *Flip*: This provides a flip transition.

We can add page transitions in the following two different ways:

1. Add a data-transition attribute to the link, using `<a href="index.html" data-transition="pop" data-back="true">`
2. Use the data-transition attribute on static pages. Programmatically, we can use

```
$.mobile.
```

```
changePage("pendingtasks.html", "slideup");
```



By: Vikas Awasthy

The author currently works as an applications developer (J2EE) in IBM India Pvt Ltd. This article is dedicated to his late mother, Smt. Krishna Sharma, and his family.