

You will see that you are inside the newly created directory.

—Sachin Patil,
icoolster@gmail.com



Resizing the Linux partition

This tip will help you to resize your partition easily in just a few steps, without the need to reinstall the operating system again.



Note: It is recommended to take back-ups of the files before trying to resize your partition.

Open up a terminal and run the following command:

```
$ sudo init 1
```

The 'init' command will load *runlevel 1*, which is used to carry out administrative operations like maintenance or emergency repairs.

Here, we are going to extend the root partition using free space from the home partition to make space for data in the root folder. The partition should be a logical volume (which is more flexible than other partition schemes) and of file system type *ext3/ext4*.

Inside *runlevel 1*, run the following commands:

```
$ cd /  
$ umount /home
```

Here, we are changing our directory to root so that we can *umount /home* and modify the partition's size.

```
$ e2fsck -f /dev/debian/home
```

Run *e2fsck*, a file system utility that checks for bad sectors and I/O errors related to HDD. This helps in fixing errors in the file system.

```
$ resize2fs /dev/debian/home 'size'G  
$ lvresize -L 'size'G /dev/debian/home
```

Replace 'size' with the value of your choice (in GB). This will shrink and resize the */home* partition to the specified 'size'.

```
$ mount -a
```

This command will mount all the partitions mentioned in *fstab (/etc/fstab)*. *fstab* lists all the available disks and disk partitions.

```
$ lvextend -L +'root_size'G /dev/debian/root
```

```
$ resize2fs /dev/debian/root
```

Here we are appending 'root_size' (in GB) to the root partition. Replace 'root_size' with the value you want to append to the root partition.

```
$ init 5
```

The above command will restart the system normally. Now you have successfully resized your partition without reinstalling the operating system.

—Jackson Isaac,
jacksonisaac2008@gmail.com



Creating a custom telnet or SSH welcome message using motd (message of the day)

This tip can be used to protect remote logins by displaying a warning to unauthorised users or a welcome message to authorised users.

Let's begin with protecting telnet/SSH logins by displaying a warning message. Log in to your server as the root via SSH:

```
sudo vi /etc/motd
```

Now type in the message you want everyone to see:

```
##### Welcome to swapnil's Ubuntu Sever #####  
###  
### WARNING : This machine is restricted to ABC Server TEAM ###  
###  
#####
```

Save and quit. Log out of SSH and then log back in; you will see your new greeting message on your terminal!

—Swapnil Kulkarni,
kulkarni.swapnil.v@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.