

```
public static void main(String[] args){

    MyThread t = new MyThread("Vikas");// line 9
    t.start();

}
```

In the above code, we have used the thread class constructor that takes *java.lang.String* as a parameter (line number 9). This gives a call to the constructor at line number 6, which further sets the name to the super class thread constructor. The output of the program is "Vikas".

```
class MyRunnable implements Runnable{

    public void run(){
        System.out.println(Thread.currentThread().getName());
    }

    public static void main(String[] args){

        MyRunnable r = new MyRunnable();
```

```
Thread t = new Thread(r, "Vikas");// line 7
t.start();

}
```

In the above code, we are trying to set the name of the thread at line number 7, which takes two parameters, *MyRunnable* object and the *java.lang.String* object. The output of the code is "Vikas".

2. By the *setName()* method of the thread class:

```
Class MyThread extends Thread{

    public void run(){

        System.out.println(Thread.currentThread().getName());
    }

    Public static void main(String[] args){

        MyThread t = new MyThread();
        t.setName("Vikas");// line 7
        t.start();
    }

}
```

In the above code we are trying to set the name of the thread at line number 7 by using the *setName()* method of thread class. The output of the code is "Vikas".

To summarise, a thread is a Java class that is present inside the *java.lang* package. There is one thread per call stack and vice versa. Every Java program has a thread running by default and it is called the Main thread, which controls the *main()* function of the Java program. There are two types of threads in Java — one is the user thread and the other is the daemon thread. The best example of a daemon thread is the garbage collector. The user thread is created by the programmer and when its execution is complete, the daemon thread is invoked by the JVM. Each Java thread has five life cycle states (Figure 1). A Java programmer can name a thread by using the thread class constructor and the *setName()* method of the thread class. 

By: Vikas Kumar Gautam

The author is a mentor at Emerx Information Technology (P) Ltd. His main areas of expertise include application development using Java/J2EE and Android for both Web and mobile devices. A Sun Certified Java Professional (SCJP), his interests include acquiring greater expertise in the application space by learning from the latest happenings in the industry. He can be reached at vikash_kumar@emertxe.com

**KNOW THE MARKET
BUY & SELL PRODUCTS
FIND A CHANNEL PARTNER
KNOW THE TRENDS
All this and more in...**



India's First Electronics Sourcing Magazine

DON'T MISS THESE FEATURES

- Latest Products
- Latest Technologies
- Trends
- Latest Innovations
- Business Potential
- Emerging Sectors
- What's In, What's Out

These will help you take the right business decisions

So don't miss out on any of the issues

SUBSCRIBE IT AND GET HEAVY DISCOUNT

CALL +91-011-26810601/02/03 FAX +91-011-26817563, 26812312
EMAIL myeb@efyindia.com WEBSITE www.eb.efyindia.com



EFY ENTERPRISES PVT LTD
D-871, Okhla Industrial Area, Phase-1, New Delhi-110020