

```
$ sudo yum install cabal-install
```

Haskell software programs are available at *hackage.haskell.org*, and each project has a *.cabal* file. Let us look at the example of the HSH-2.1.2 package at <http://hackage.haskell.org/package/HSH> which allows you to use shell commands and expressions within Haskell programs. You can download the *HSH-2.1.2.tar.gz* and extract it using:

```
$ tar xzvf HSH-2.1.2.tar.gz
```

```
HSH-2.1.2/
HSH-2.1.2/COPYING
HSH-2.1.2/HSH.cabal
HSH-2.1.2/testsrc/
HSH-2.1.2/testsrc/runtests.hs
HSH-2.1.2/HSH.hs
HSH-2.1.2/HSH/
HSH-2.1.2/HSH/Command.hs
HSH-2.1.2/HSH/ShellEquivs.hs
HSH-2.1.2/HSH/Channel.hs
HSH-2.1.2/COPYRIGHT
HSH-2.1.2/Setup.lhs
```

The *.cabal* file has various fields that describe the Haskell application. The contents of the *HSH.cabal* for version 2.1.2 are given below:

```
Name: HSH
Version: 2.1.3
License: LGPL
Maintainer: John Goerzen <jgoerzen@complete.org>
Author: John Goerzen
Stability: Beta
Copyright: Copyright (c) 2006-2014 John Goerzen
Category: system
license-file: COPYRIGHT
extra-source-files: COPYING
homepage: http://software.complete.org/hsh
Synopsis: Library to mix shell scripting with Haskell
programs
```

```
Description: HSH is designed to let you mix and match shell
expressions with
```

```
Haskell programs. With HSH, it is possible to easily run
shell
commands, capture their output or provide their input, and
pipe them
to and from other shell commands and arbitrary Haskell
functions at will.
```

```
Category: System
```

```
Cabal-Version: >=1.2.3
```

```
Build-type: Simple
```

```
flag buildtests
```

```
description: Build the executable to run unit tests
default: False
```

```
library
```

```
Exposed-Modules: HSH, HSH.Command, HSH.ShellEquivs, HSH.
```

```
Channel
```

```
Extensions: ExistentialQuantification, OverlappingInstances,
UndecidableInstances, FlexibleContexts, CPP
Build-Depends: base >= 4 && < 5, mtl, process, regex-
compat, MissingH>=1.0.0,
hslogger, filepath, regex-base, regex-posix, directory,
bytestring
if !os(windows)
Build-Depends: unix
GHC-Options: -O2 -threaded -Wall
```

```
Executable runtests
```

```
if flag(buildtests)
```

```
Buildable: True
Build-Depends: base >= 4 && < 5, mtl, process, regex-
compat,
MissingH>=1.0.0,
hslogger, filepath, regex-base, regex-posix, directory,
bytestring, HUnit, testpack
if !os(windows)
Build-Depends: unix
else
Buildable: False
Main-Is: runtests.hs
HS-Source-Dirs: testsrc, .
Extensions: ExistentialQuantification, OverlappingInstances,
UndecidableInstances, FlexibleContexts, CPP
GHC-Options: -O2 -threaded
```

Enter the *HSH-2.1.2* directory and configure the project using the *cabal configure* command as shown below:

```
$ cd HSH-2.1.2
```

```
$ cabal configure
Resolving dependencies...
Configuring HSH-2.1.2...
```

You can then compile the project sources using the *cabal build* step:

```
$ cabal build
```

```
Building HSH-2.1.2...
Preprocessing library HSH-2.1.2...
```