

The output is:

```
$ chkconfig --list vsftpd
vsftpd 0:off 1:off 2:off 3:off 4:off 5:off 6:off
```

To overcome this and to configure the service to start automatically, you can use:

```
chkconfig vsftpd on
```

To confirm, run the command given below:

```
$ chkconfig --list vsftpd
vsftpd 0:off 1:off 2:on 3:on 4:on 5:on 6:off
```

Adding FTP users

Now, your FTP server is ready to use and you can add users who can access it. Adding FTP users is very similar to adding users in the operating system, using the `useradd` command. With this, every user will get a separate home directory and with the `chroot` jail activated, users will be forced to work within their home directories.

To add the user 'mandar', simply run:

```
useradd mandar
```

To set the password for 'mandar', use the `passwd` command as follows:

```
passwd mandar
```

You will have to mention the new password and confirm it once:

```
Changing password for user mandar.
```

```
New password:
```

```
Retype new password:
```

```
passwd: all authentication tokens updated successfully.
```

Now, the user 'mandar' will be able to use the FTPS services with any FTP client that supports SSL/TLS, such as FileZilla. In order to access the FTPS server through browsers, you may require to install some add-ons like 'fireFTP'.

You can limit access to the FTPS server, but allow people to use FTPS services at the same time, by changing their shell to `/sbin/nologin`. Further, you can set a password policy for the users (`/etc/pam.d/system-auth`) to make them select a strong password and change it regularly (`chage` command). 

By: Mandar Shinde

The author works in the IT division of one of the largest commercial automotive organisations in India. His technical interests include Linux, networking, backups and virtualisation.

...Continued from page 65

```
salt '*' saltutil.refresh_pillar
```

```
salt '*' pillar.items users ( you should see the users from
the output)
```

```
minion:
```

```
-----
users:
-----
john:
    1000
henry:
    1001
pal:
    1002
```

You can create users by using the pillar data .sls file, as follows:

```
/srv/salt/users/init.sls
{% for user, uid in pillar.get('users', {}).items() %}
{{user}}:
```

```
user.present:
- uid: {{uid}}
{% endfor %}
```

So this is the last in the series of three articles on SaltStack. We do hope you enjoyed reading these articles as much as we did putting them together for you. 

References

- [1] <http://www.wekanban.com/saltstack-targeting-minion-part-5/>
- [2] <http://docs.saltstack.com>
- [3] <http://salt.readthedocs.org>
- [4] <https://wikitech.wikimedia.org/wiki/Salt>

By: Bejoy Abraham Mathews and Davana Satish Gongadi

Bejoy Abraham Mathews works with Servista Inc. He has earlier authored articles on Puppet and has RHCE, cloud and Big Data certification. He can be contacted at bejoy.abraham@gmail.com

Davana Satish Gongadi works with Quadrant 4 System Corporation. He is SCJP certified and is an expert on Java Application Server environments in GNU/Linux. He can be contacted at gd_satish@yahoo.com.