



TIPS & TRICKS



Reading emails using 'telnet'

Have you ever read emails using telnet? Here are the steps to do so:

```
# telnet mail.example.com 110
```

110 is the port number for the POP3 connection. Just connect to the mail server using 110. You will get the following response:

```
Trying 192.168.1.1...
Connected to mail.example.com.
Escape character is '^J'.
+OK Hello there.
```

Then provide the user login details, as follows:

```
# user test@example.com
```

The response message you get is given below:

```
+OK Password required.
```

Then provide the password:

```
# pass Test@123
```

Shown below is the response message:

```
+OK logged in.
```

Now, use the following command to see the emails:

```
# list
```

Here's the response message:

```
1 3899
2 3894
```

To read the first email, use the following command:

```
#retr 1
```

To delete the emails, use the command:

```
#dele 1
```

Some servers won't respond to telnet requests, in which case, these commands cannot be used.

—Nivas Baskaran,
bnivas@live.in



Change your desktop's wallpaper automatically

To change your desktop environment, all you have to do is run the following script with a directory name containing *wallpapers(jpg)* as the argument. The script will select a wallpaper at random and set it as your wallpaper.

```
#!/bin/sh
setbackground="gsettings set org.gnome.desktop.background
picture-uri file://"

if [ $# != 1 ]
then
echo "`readlink -f $0`: No Arguments supplied."
echo "Please give a directory containing the wallpapers or
images."
exit -1
fi
wallpapertimeout=300
pathname=$1
if [ ! -d $pathname ]
then
echo "$pathname is not a directory"
exit -1
fi
if [ $pathname == "." ]
then
pathname=`pwd`
fi
if [ $pathname == ".." ]
then
pathname=`dirname $PWD`
fi
```