

```
echo "Got the directory name as $pathname"
```

```
filecount=`ls -l $pathname/*.jpg | wc -l`
```

```
if [ $filecount == 0 ]
```

```
then
```

```
echo "No of wallpapers or images in the directory $pathname  
is zero"
```

```
exit -1
```

```
fi
```

```
echo "No of files in the directory is $filecount"
```

```
filelist=`ls $pathname/*.jpg`
```

```
while [ 1 ]
```

```
do
```

```
j=1
```

```
rndnum=$((RANDOM % $filecount + 1 | bc))
```

```
for i in `ls $pathname/*.jpg`
```

```
do
```

```
if [ $j == $rndnum ]
```

```
then
```

```
echo "Got match for $i"
```

```
`setbackground $i`
```

```
fi
```

```
j=$((j+1))
```

```
done
```

```
sleep $wallpapertimeout
```

```
done
```

—Rajeev N Sambhu,
rajnellaya@gmail.com



Disabling the password prompt for *sudo* users

Often, GNU/Linux users come across the *sudo* utility. But on executing any command with *sudo* requests, users have to provide their own passwords once, which can then be used afterwards.

```
$ sudo vim /etc/sudoers
```

```
[sudo] password for tom:
```

To disable this *sudo* password prompt, edit the */etc/sudoers* file as follows:

```
sudo vim /etc/sudoers
```

and change...

```
%sudo    ALL=(ALL:ALL) ALL
```

```
...to
```

```
%sudo    ALL=(ALL:ALL) NOPASSWD: ALL
```

Save the file and check for the changes. You are now free to execute anything without entering passwords.

—Anoop C S,
anoopc9@gmail.com



Using the *lsdf* command

lsdf lists an open file, which could be a regular file, a directory, a block special file, a character special file, an executing text reference, a library or a stream.

Shown below are a few of the options of *lsdf* along with some information on what they do.

```
#lsdf
```

This is to see all the open files in a system without filtering. The command lists all open files belonging to active processes.

```
#lsdf -i TCP:ftp
```

Sometimes, we face issues like a service that will not bind to a port and, hence, cannot start. This is due to some process already using that port (though the process died). So we have to see which process is using the port, and kill it. This will avoid the need to restart the server. Let's assume that we want to start the ftp server, which is not starting due to the above problem.

```
#lsdf -c httpd
```

The above command is to see what files are open when you execute a command. Here, *-c* is for specifying the command.

```
#watch lsdf -i
```

The above command is to monitor the network -- to keep a tab on what people are doing with particular network services.

```
#lsdf /dev/hdcUSAGES
```

This is to see which file opened for a device.

```
#lsdf -i -U
```

This is to see all open Internet files.

```
#lsdf -f filename
```

This last command is to see which process or user is accessing the file.

—AkhilRaj P V,
akhilrajpv07@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.