



Figure 4: Eclipse code recommenders



Figure 5: Java Web project

Name as *FirstJavaProject* in the dialogue box.

Select *Use default location* in the checkbox. Then select *Execution Environment JRE* (if you want to configure JRE, then click on the link *Configure JREs*) and click on *Next*.

Verify the source folder. By default, it will be an `src` folder and the default output folder will be `FirstJavaProject/bin`, in our case.

Check the *Library* tab to verify the JRE system library available for *JavaProject*. Add JARs or

external JARs if you want to.
Click on *Finish*.

To create a package in a Java project, right-click on the src folder of *FirstJavaProject* in *Package Explorer*. Click on *New* → *Package*. Select *Source Folder* in the new dialogue box and provide the name of the package as 'com.igate.test'. Click *OK*.

To create a class in a newly-created package, right-click on the package `com.igate.test`. Click on *Class*, and give the name of the new Java class as *HelloWorld*. Keep the modifier public, as it is, except if you want to make that class abstract or final. Select the checkbox *Public static void main (String[] args)* in the ‘Which method stubs would you like to create?’ section.

It will create a class in the package 'com.igate.test' with method public static void *main*(String[] args). Add the print statement in the main method.

To generate a comment for any method, keep the cursor on the name of the method and press **Alt+Shift+j**.

Normally, over time, we use a lot of import statements in our programs; so to arrange them in a proper way, press *Ctrl+Shift+o*.

```
package com.igate.test;

public class HelloWorld {

    String name;

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    /**
     * @param args
     */
    public static void main(String[] args) {

    }

}
```

To create an interface in a newly created package, right click on the package 'com.igate.test'. Click on *Interface*.

To create a pair of getter and setter methods, right click on the class variable name. Go to *Source* → *Generate getters and setters*. Select the variable name to create methods from the dialogue box. Select *Access Modifiers*. Click on *OK*.

To give a proper indent to the code in a *.java* file, select all the content of the file and press *Ctrl+i*.

To format the code with proper spacing, press **Ctrl+Shift+f**.

Using code recommenders

Code templates help programmers to reduce their typing efforts by inserting code into the Eclipse editor. Type the short code and press *Ctrl + space* to get a dialogue box to select a code template.

Running a Java application

To run the Java project, right click on the *FirstJavaProject*. Click on *Run As* → *Java Application*. Check the output in the console.

To change the run configurations, right click on the *FirstJavaProject*. Click on *Run As*. Select *Run Configurations*.

Here, you can give program and VM arguments, set the runtime JREs, as well as set the class path and environment variables, etc.