



TIPS & TRICKS



Abort unwanted AJAX requests

We do many AJAX requests in our Web applications. Sometimes, many of these AJAX requests become invalid before they receive the data. For example, on auto complete, if we type each character, an AJAX request is raised to get the suggestion. But only the last AJAX request with the complete word will be considered as a suggestion, and all other AJAX requests just receive the data, which they drop.

To avoid this, we can abort the previous AJAX handler before making the next AJAX request by using the following code:

```
$( document ).ajaxSend(function(event, jqxhr, settings) {  
  
    var url = settings.url;  
  
    if (url.indexOf("search") > -1 ) { //select the  
request by URL content  
  
        if(typeof _lastAjaxReq != 'undefined') {  
  
            _lastAjaxReq.abort();  
  
        }  
  
        _lastAjaxReq = jqxhr;  
  
    }  
  
});
```

—Balavignesh Kasinathan,
kbalavignesh@gmail.com



Manipulating NIC parameters

Many of us do not know that we can manipulate the parameters associated with network interface cards (NIC). *ethtool* is a tool that can help you change settings.

To display network statistics, use the following command:

```
#ethtool -S eth0
```

For auto-negotiation *on/off*, use the following commands:

```
#ethtool -s eth0 autoneg off  
#ethtool -s eth0 autoneg on
```

To change the speed of the Ethernet device, use this command:

```
#ethtool -s eth0 speed 100 autoneg off
```

To see the current NIC ring buffer settings, type:

```
#ethtool -g eth0
```

To change the tx and rx ring buffer size of the NIC, use this command:

```
#ethtool -G -set-ring eth0 rx N1 rx-min N2 tx N3
```

—Gaurav Datir,
gauravsdattir@gmail.com



Delete files older than a particular period

Files that are older than a particular day can be deleted easily with a one line command. For example, the following command will delete files older than 30 days in the path */tmpboot/*:

```
#find /tmpboot/* -mtime +30 -exec rm {} \;
```

—Suraj Tamilselvan,
surajluz@gmail.com



How to find opened files used by someone at a particular time

When running *top -c* and typing *SHIFT P* (to display the descending order of processor usage), if you find that a