

user is taking up too much of the resources, you can find the opened files used by that person by executing the following command:

```
for i in `ps aux | grep <username> | awk '{print $2}'`; do  
lsof -p $i ; done
```

In the above command `<username>` is the name of the user.

This will be helpful in troubleshooting, in case a suspicious file is opened by a user.



Script to find the site speed

Here is a simple script that uses CURL to check the speed of a website. You need to log in as the root user and create a file as follows:

```
# touch speedcheck.sh
```

Now, open the file in any text editor and add the following lines:

```
#!/bin/bash  
CURL="/usr/bin/curl"  
GAWK="/usr/bin/gawk"  
echo -n "Please pass the url you want to measure: "  
read url  
URL="$url"  
result=$(CURL -o /dev/null -s -w %{time_connect}:%{time_starttransfer}:%{time_total} $URL)  
echo " Time_Connect Time_startTransfer Time_total "  
echo $result | GAWK -F: '{ print $1" "$2" "$3}'
```

Save and exit.

Run the script and wait for some time to get the output:

```
# sh speedcheck.sh
```

The output will be in the format given below:

```
time_connect:time_starttransfer:time_total
```

—Paul Jany,
pauljanygodwin@gmail.com



Customise your shell prompt

The shell can be customised according to your requirements. All you need to do is to edit `~/.bashrc` and add your customisation.

The default value of PS1 on RHEL 5.X systems looks like what follows:

```
PS1='\u@\H:\w\$ '
```

...which results in a shell prompt like what is shown below:

```
user@hostname[FQDN]:/Current/Working/Directory$
```

If you want to add some colours to your prompt, you can try the following command:

```
PS1='\[\033[02;32m\]\u@\H:\[\033[02;31m\]\w\$'\[\033[33m\]  
,
```

For some more variants of colour codes, you can try out the following options:

```
clear  
echo -e "\033[1m" Open Source For You "\033[0m"  
echo -e "\033[5m" Open Source For You "\033[0m"  
echo -e "\033[7m" Open Source For You "\033[0m"  
echo -e "\033[30m" Open Source For You "\033[0m"  
echo -e "\033[31m" Open Source For You "\033[0m"  
echo -e "\033[32m" Open Source For You "\033[0m"  
echo -e "\033[33m" Open Source For You "\033[0m"  
echo -e "\033[34m" Open Source For You "\033[0m"  
echo -e "\033[35m" Open Source For You "\033[0m"  
echo -e "\033[36m" Open Source For You "\033[0m"  
echo -e "\033[41m" Open Source For You "\033[0m"  
echo -e "\033[42m" Open Source For You "\033[0m"  
echo -e "\033[43m" Open Source For You "\033[0m"  
echo -e "\033[44m" Open Source For You "\033[0m"  
echo -e "\033[45m" Open Source For You "\033[0m"  
echo -e "\033[46m" Open Source For You "\033[0m"  
echo -e "\033[47m" Open Source For You "\033[0m"
```

If you want to make the changes for all users of the system, then do these in the `/etc/bashrc` file. Comment out the default settings and add your customisation as below:

```
# [ "$PS1" = "\s-\v\\\$ " ] && PS1='\u@\H:\w\$ '  
PS1='\u@\H:\w\$ '
```

—Rahul Pahade,
rahul.pahade@gmail.com

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.