

```
rm -f $PEM1 $PEM2
Generating a 2048 bit RSA private key
.....+++
.....+++
writing new private key to '/tmp/openssl.4L2n3J'
-----
```

You will be asked to enter information that will be incorporated in your certificate request.

What you will enter is called a 'distinguished name' or a DN. There are quite a few fields but you can leave some blank. For some fields, there will be a default value. If you enter '.', the field will be left blank.

```
Country Name (2 letter code) [XX]:IN
State or Province Name (full name) [:]:MAHARASHTRA
Locality Name (eg, city) [Default City]:PUNE
Organization Name (eg, company) [Default Company Ltd]:OSFY
Organizational Unit Name (eg, section) [:]:PUBLISHING
Common Name (eg, your name or your server's hostname)
[:]:PILOTVM01
Email Address [:]:arindam0310018@gmail.com
[root@pilotvm01 certs]#

[root@pilotvm01 certs]#ll
total 1224
-rw-r--r--. 1 root root 578465 Apr 7 2010 ca-
bundle.crt
-rw-r--r--. 1 root root 658225 Apr 7 2010 ca-
bundle.trust.crt
-rwxr-xr-x. 1 root root 610 Feb 10 2011 make-
dummy-cert
-rw-r--r--. 1 root root 2242 Feb 10 2011 Makefile
-rw----- 1 root root 3141 May 18 11:14
pilotvm01.pem
[root@pilotvm01 certs]#
```

Now rename the certificate from *pilotvm01.pem* as *cacert*.
pem while copying it to */etc/Postfix*:

```
[root@pilotvm01 certs]#cp pilotvm01.pem /etc/Postfix/cacert.pem
[root@pilotvm01 certs]#cd
[root@pilotvm01 ~]#
```

Verify if the Postfix Service is running, as follows:

```
[root@pilotvm01 ~]#service Postfix status
master (pid 2093) is running...
[root@pilotvm01 ~]#
```

After verification, restart the Postfix Service:

```
[root@pilotvm01 ~]#service postfix restart
```

```
Shutting down postfix: [ OK ]
Starting postfix: [ OK ]
[root@pilotvm01 ~]#
```

Now, let's try sending email.

1. To send email as the root user, type:

```
echo "This is message body" | mail -s "This is Subject"
<VALID EMAIL ADDRESS>
```

Example:

```
[root@pilotvm01 ~]#echo "This is the message body" | mail -s
"This is the Subject" mail2arindam2003@yahoo.com
```

Observation:

On receiving email, the 'From Address' is displayed as
'root arindam0310018@gmail.com'.

2. Now let's create a normal user 'adminlinux' and then send email:

```
[root@pilotvm01 ~]#useradd adminlinux
[root@pilotvm01 ~]#su - adminlinux
```

```
[adminLinux@pilotvm01 ~]$pwd
/home/adminLinux
[adminLinux@pilotvm01 ~]$
```

```
[adminLinux@pilotvm01 ~]$echo «This is the message body» |
mail -s «This is the Subject» mail2arindam2003@yahoo.com
[adminLinux@pilotvm01 ~]$
```

Observation:

On receiving email, the 'From Address' is displayed as
<arindam0310018@gmail.com>.

3. To send email with attachments as user *adminlinux*, type:

```
[adminLinux@pilotvm01 ~]$echo "This is message body" | mail
-s "This is Subject" -r "Arindam-arindam0310018@gmail.com">
-a /root/df.txt mail2arindam2003@yahoo.com
```



Note: 1. With the *-r* option, the 'from' name and address can be specified.

2. With the *-a* option, attachments can be added.



By: Arindam Mitra

The author is assistant manager in a Pune-based IT company. You can contact him at mail2arindam2003@yahoo.com or arindam0310018@gmail.com