

Nagios server: 192.168.0.109
Operating system: Red Hat Enterprise Linux 6.5
Nagios client: 192.168.0.108
Operating system: Red Hat Enterprise Linux 6.5
Nagios Core version: 4.0.8
Nagios plugins version: 2.0.3

Nagios Core installation

Installing the necessary packages and their dependencies:

The required packages mainly include Apache, PHP, C compilers, C libraries and development libraries. These packages can be installed using the Yum install as shown below:

```
$ yum install wget httpd php gcc glibc glibc-common gd gd-devel
make net-snmp
```

In order to make sure that the service 'httpd' starts after every system reboot, it should be added to the startup as follows:

```
$ chkconfig httpd on
$ service httpd start
```

Downloading the Nagios Core and Nagios plugins packages:

After the installation of the required packages, it's time to download Nagios Core and Nagios plugins, which are available in the form of tarballs, from the official website.

```
$ cd /root
$ wget http://prdownloads.sourceforge.net/sourceforge/nagios/
nagios-4.0.8.tar.gz
$ wget http://nagios-plugins.org/download/nagios-plugins-
2.0.3.tar.gz
```

Adding the 'nagios' user and 'nagios' group: In order to submit and process external commands from the graphical user interface, we need to create a group, say 'nagios', and add a user, say 'nagios', to that group.

```
$ groupadd nagios
$ useradd -g nagios nagios
```

Nagios Core installation: Having downloaded the Nagios Core tarball file from the source, we will have to extract it in order to proceed with the installation.

```
$ tar -xvzf nagios-4.0.8.tar.gz
```

Change to the `nagios-4.0.8` directory to begin the configuration part. After executing the 'configure' script, we have to compile the source code and then install it.

```
$ cd nagios-4.0.8
$ ./configure --with-command-group=nagios
```



Figure 1: Nagios-Web console

```
$ make all
$ make install
$ make install-init
$ make install-config
$ make install-commandmode
$ make install-webconf
```

Now, restart the httpd service for the changes to take effect.

```
$ service httpd restart
```

To make sure that the 'nagios' service starts after every system reboot, we must add it to the startup services as follows:

```
$ chkconfig nagios on
```

Nagios plugins installation: In order to monitor remote hosts and the services running on them, we need to install Nagios plugins. For this, we need to change to the 'nagios-plugins-2.0.3' directory, run the 'configure' script, make and install the binaries.

```
$ cd nagios-plugins-2.0.3
$ ./configure --with-nagios-user=nagios --with-nagios-
group=nagios
$ make
$ make install
```

Nagios Web access: We are almost done with the installation part and to verify if it is correct, you can open your Web browser and enter `http://<NAGIOS-SERVER-IP-ADDRESS>/nagios`

You will find a dialog box asking for your credentials in order to access the Nagios Web interface (Figure 1).

So far, we've not created any login to access the Nagios

Web interface. Let's create it now.

```
$ httpasswd -c /
usr/local/nagios/
etc/httpasswd.users
<USERNAME>
```

You'll be asked to enter the password and then confirm it before a login is created.




Figure 2: Nagios unable to get process status