In the above JSON file, the record field represents the actual record and the ID field represents the number (record number).

Now, let's insert the *test.json* file in MongoDB using Python:

```
import json
import pymongo
connection = pymongo.MongoClient("mongodb://localhost")
db=connection.book
record1 = db.bookcollection
page = open("test.json", 'r')
parsed = json.loads(page.read())

for item in parsed["Records"]:
    record1.insert(item)
```

Run the code using the following command:

```
# python insert.py
```

Just be sure that *test.json* is present in the same directory.

Now, let's go over each and every line.

The first two lines are importing the *json* and *pymongo* module.

Code line connection = pymongo.MongoClient ("mongodb://localhost") establishes a connection to the database. The next line is *db=connection.book handle to the book database. Code line record1 = db.bookcollection;* here, *record1* contains a collection of records. In the next line, *page = open ("test.json", 'r')* the variable *page* contains the *test.json* file. And in the following line, the variable *parsed* contains the file in *json* format. If you want to view the records from the MongoDB command line, use the commands as shown below.

The code line for the item in *parsed["Records"];* shows that we are interested in *parsed["Records"]*. The last line inserts the records one by one in *record1 collection*.

If you want to view the records from the MongoDB command line, use the following command:

```
# use book
# db.bookcollection.find()
```

Find the data with Python

In the previous code snippet, we inserted the records in the *record1 collection of books* database. Now we are going to discuss the code to view the records.

Here is the minimum code named *using_find.py* to view the records:

```
import pymongo
connection = pymongo.MongoClient("mongodb://localhost")
db=connection.book
record1 = db.bookcollection
cursor = record1.find()
for doc in cursor:
     print doc
```

I think you are acquainted with the first four lines. Code line *cursor = record1.find()* tells the cursor to contain all the records. If you print the *cursor* variable, it will give you addresses like *<pymongo.cursor.Cursor object at 0x1aac810>*

In order to print the *cursor* document, we have used the *for* loop.

Run the program and you will get the output shown in Figure 1.

Let's assume that you want to display a particular field. Make some amendments to the above code. Replace the following line…

```
cursor = record1.find()
```

...with

```
cursor = mo.find({},{«ID»:True,
«_id»:False})
```

…and run the program again. The output will be like what's shown in Figure 2.




Figure 1: Output shows the records of *bookcollection*



Figure 2: Output shows the specific field



Figure 3: Output shows the specific document (record)