

To restart iptables use the following command:

```
service iptables restart
```

To add rules to the existing iptables to allow ssh, use the following command:

```
iptables -A INPUT -i eth0 -p tcp --dport 22 -j ACCEPT
```

Option	Explanation
-A INPUT	To add or append a rule to the INPUT chain for incoming traffic
-i eth0	Incoming packets through the interface eth0 will be verified against this newly added rule
-p tcp --dport 22	Protocol is TCP and the destination port is 22
-j ACCEPT	ACCEPTS the packet

You can verify modified set of rules by seeing /etc/sysconfig/iptables file (as shown in Figure 10).

A few examples to make you comfortable with iptables

1. To allow HTTP traffic, use the following command:

```
iptables -A INPUT -p tcp -m state --state NEW -m tcp --dport 80 -j ACCEPT
```

2. To allow HTTPS traffic, use the following command:

```
iptables -A INPUT -s 9.9.9.9 -p tcp -m state --state NEW -m tcp --dport 443 -j ACCEPT
```

3. To allow SSH traffic, use the following command:

```
iptables -A INPUT -i eth0 -p tcp --dport 22 -m state --state NEW,ESTABLISHED -j ACCEPT
iptables -A OUTPUT -o eth0 -p tcp --sport 22 -m state --state ESTABLISHED -j ACCEPT
```

4. To allow SNMP traffic, use the following command:

```
iptables -A INPUT -p udp -m state --state NEW -m udp --dport 161 -j ACCEPT
```




Figure 6: Stopping and starting iptables




Figure 7: /etc/sysconfig/iptables



Figure 8: Restarting iptables



Figure 9: Appending a rule




Figure 10: /etc/sysconfig/iptables after adding a rule

5. To change the default chain policies, use these commands:

```
iptables -P INPUT DROP
```