

Micromax Unite 2 gets Android 5.0 Lollipop update


Indian smartphone maker Micromax has announced an Android 5.0 Lollipop update for its Unite 2 smartphone in the country. The Micromax Unite 2 was one of the first smartphones from the company to get a promised upgrade to Android Lollipop and the update went live over-the-air from April 7, 2015. The update will automatically reach Unite 2 devices; however, users will also be able to trigger it by going to *Settings > About Phone > Software Update*.

The company has not shared an official update change-log at this point, but users can expect to see the usual Lollipop changes like UI improvements, enhanced notifications, better performance, battery-life improvements and more. Micromax has also revealed that Unite 2, one of its most successful smartphones, has sold over 1.5 million units within a year of launch. The Unite 2 smartphone is an entry-level release and it is selling for around Rs 5600 through online retailers. It comes with a simple design in a choice of attractive colours like pristine white, balmy green, mystic grey and raging red. These rear shells can also be easily swapped for customised options.

"Launched with the aim to remove the language barrier in the country, Unite 2 was the world's first phone with support for 21 languages. The sales figures of the smartphone highlight the need for a more efficient technological experience, which gives the masses the freedom to communicate through their phones in the comfort of their native language," a Micromax press release stated.



Calibre 2.22 now available for download



The creator of Calibre, Kovid Goyal, has announced the availability of Calibre 2.22 for download. The new release of this open source e-book library manager for GNU/Linux, Mac OS X and Microsoft Windows operating systems introduces a number of new features, as well as multiple bug fixes.

Calibre 2.22 allows users to expand the editor widget when editing data in the Book List component in order to use all the available width. Users can also restore opened files, as well

as the position of the text cursor when reopening previously edited books. And there is support for adding weeks, days, years and months in the advanced search builder.

Calibre 2.22 also supports updating of metadata in DOCX files, adds support for intra-document cross-references in the ODT input, makes the Amazon metadata download functionality faster, and repairs wrong ASCII control characters encoding as well as strange Chinese characters in the ToC (Table of Contents) and metadata strings. It addresses some issues in the Manage Authors dialogue box, which caused the current Book List search to be cleared.

The new version has repaired an issue in the Amazon metadata download functionality. Another issue fixed in the new Calibre version is regression in the previous Calibre version 2.21, which caused the conversion process to fail when using books that had an invalid pseudo-class CSS selector.

Besides, the Open Publication Distribution System (OPDS) categories have been patched to display books for composite column categories even if the respective column includes a colon, an error has been fixed when scanning default applications on the Microsoft Windows OS for various file types, some Preview

PEEDI JTAG Debugger

(Powerful Embedded Ethernet Debug Interface)



PEEDI is an Embedded ICE solution that enables you to debug software running on ARM, CORTEX-M0 /M3/M4/A5/A8/A9, PowerPC, XScale, Coldfire, Blackfin, AVR32, MIPS32 processor cores via the JTAG/BDM/SWD port. PEEDI provides the services needed to perform all debugging operations.

Key Features:

- Wide Processor support: ARM, Cortex, PowerPC, XScale, Coldfire, Blackfin, AVR32, MIPS32 etc.
- Multi Core support
- Linux Kernel and applications debugging
- OS awareness - "info threads" support for many OS: Linux, uClinux, eCos, ...
- Blackfin virtual memory support - enables a linear programming and access to a device that is bigger than the visible external asynchronous memory space
- Built in FLASH Programmer (can be used as a Standalone FLASH programmer without host)
- Front panel interface: 2 buttons and 7 segment LED
- Ability to route the RS232 of the PEEDI to a TCP/IP port
- Ability to route the ARM7/ARM9/ Cortex-M3 DCC to a TCP/IP port
- Economical

WARRANTY:
Hardware 3 Years;
Software 1 Year



Uchi Embedded Solutions

Bangalore - 560032.
Ph: 080-42146669, Cell: 9986016902
Email: sales@uchiembedded.co.in

www.uchiembedded.co.in