

```
0114405f9ff1: Download complete
511136ea3c5a: Download complete
b6718650e87e: Download complete
3d3c8202a574: Download complete
Status: Downloaded newer image for centos:latest
[root@teja-dev-vm01 ~]#
[root@teja-dev-vm01 ~]# docker run -t -i centos /bin/bash
[root@19de0ebc88f7 /]#
[root@19de0ebc88f7 /]# uname -a
Linux 19de0ebc88f7 3.10.0-123.el7.x86_64 #1 SMP Mon Jun 30
12:09:22 UTC 2014 x86_64 x86_64 x86_64 GNU/Linux
[root@19de0ebc88f7 /]# exit
exit
[root@teja-dev-vm01 ~]#
```

Containers can also be started in daemon mode. Shown below is an example to start the CentOS container in daemon mode. The option `-d` is used to invoke the containers in daemon mode. In the following example, we are printing a simple text—‘Hello World’. The command `docker ps -a` shows the status of each container along with its ID. The first command in the example is to start the container and execute the command `echo Hello World` in an infinite loop. The command `docker logs <container-id>` will help us to tap into the container and see what’s happening.

```
[root@teja-dev-vm01 ~]# docker run -d centos /bin/sh -c
"while true; do echo Hello World; done"
c9be70db3e2729ae4653fd61c91c6845fe8b177381392cf416dcfa4f2d659f
[root@teja-dev-vm01 ~]#
[root@teja-dev-vm01 ~]# docker ps -a
CONTAINER ID        IMAGE               COMMAND
CREATED            STATUS              PORTS
NAMES
c9be70db3e27        centos:7           "/bin/
sh -c 'while t     4 minutes ago      Up 2 minutes
hopeful_pike
cc899c0cfd9         centos:7           "/bin/
sh -c 'while t     6 minutes ago      Up 5 minutes
dreamy_wilson
[root@teja-dev-vm01 ~]#
[root@teja-dev-vm01 ~]# docker logs c9be70db3e27
Hello World
Hello World
Hello World
Hello World
Hello World
Hello World
Hello World
^C[root@teja-dev-vm01 ~]#
```

Running containers can be stopped with the command `docker stop <container-id>`. The code below stops the container and also removes it:

```
[root@teja-dev-vm01 ~]# docker ps -a
CONTAINER ID        IMAGE               COMMAND
CREATED            STATUS              PORTS
NAMES
c9be70db3e27        centos:7           "/bin/
sh -c 'while t     19 minutes ago      Up 17 minutes
hopeful_pike
cc899c0cfd9         centos:7           "/bin/
sh -c 'while t     21 minutes ago      Up 20 minutes
dreamy_wilson
[root@teja-dev-vm01 ~]#
[root@teja-dev-vm01 ~]# docker stop c9be70db3e27
c9be70db3e27
[root@teja-dev-vm01 ~]#
[root@teja-dev-vm01 ~]# docker rm c9be70db3e27
c9be70db3e27
[root@teja-dev-vm01 ~]#
```

The LAMP stack with Docker containers can be done in two ways. The first is to download the preconfigured LAMP stack Docker image from Docker Hub, and the second option is to pull the base image and install/configure all the components of the LAMP stack.

For the first option, we will pull the `linode/lamp` image. This image is one of the popular preconfigured Docker images available on Docker Hub. The code given below searches for the image, pulls it and starts the container with all the LAMP stack components preinstalled.

```
[root@teja-dev-vm01 ~]# docker search linode
[root@teja-dev-vm01 ~]#
[root@teja-dev-vm01 ~]# docker pull linode/lamp
Pulling repository linode/lamp
115a4e1b4860: Download complete
511136ea3c5a: Download complete
27d47432a69b: Download complete
5f92234dcf1e: Download complete
51a9c7c1f8bb: Download complete
5ba9dad47459: Download complete
cfea48d8d4c8: Download complete
664027dedce4: Download complete
Status: Downloaded newer image for linode/lamp:latest
[root@teja-dev-vm01 ~]#
[root@teja-dev-vm01 ~]# sudo docker run -p 80:80 -t -i
linode/lamp /bin/bash
[root@teja-dev-vm01 ~]# sudo docker run -p 80:80 -t -i
linode/lamp /bin/bash
root@fb6c47e05cfe:/# service apache2 start
* Starting web server apache2
*
root@fb6c47e05cfe:/# service mysql start
* Starting MySQL database server mysqld
[ OK ]
* Checking for tables which need an upgrade, are corrupt or
```