

To enable auto updation again of `/etc/resolv.conf`, just remove the above entry or change its value:

```
"PEERDNS=yes".
```

Note: Replace `'ifcfg-eth<NUMBER>'` with the actual number.

—Narendra Kangralkar,
narendrakangralkar@gmail.com



Recording the shell session and replaying it

Here is a small tip that allows you to record and replay commands that you use in your shell.

The command to start recording the shell session is as follows:

```
# script -t 2> project.timing -a project.session
```

After this, all subsequent commands typed in the terminal will be recorded. To stop recording, you need to just 'Exit'.

The command to replay the recorded session is as follows:

```
# scriptreplay project.timing project.session
```

The script command does not have the 'Pause' option, but here is another way to achieve that through a Python module. First, we need to install the Python module as shown below:

```
#pip install TermRecord
```

Now, to start recording a shell session, use the following command:

```
#TermRecord -o mysession.html
```

All subsequent commands will be recorded. Finally, just 'Exit' to stop recording.

To view this, you can open the output file on any browser. This will let you play, replay and pause.

—Rajeshwaran Gopalakrishnan,
rajeshwaran@dcis.in



What shell is your Linux distribution using?

A shell is a special program that allows the user to communicate with the kernel. It accepts specific

commands and instructions, and communicates them to the kernel. There are dozens of shells for Linux and the most popular are: Bash (Bourne again shell), ksh (Korn shell), csh (c shell), ash (Almquist shell) and Dash (Debian almquist shell).

```
rames@ubuntu:~$echo $$SHELL
```

```
/bin/bash
```

Ubuntu uses the Bash shell. The dollar sign indicates the Bourne shell. Shell commands may vary from shell to shell, but Linux commands are the same for every shell though they differ from one Linux distribution to the other.

—Ramesh Mariappan,
ramesh2get@gmail.com

Use Bash to change a given string to either upper case or lower case

Let's look at the following string as an example:

```
Linux For You.
```

```
[raja@support ~]$ string="Linux For You"
```

Now, to convert it into lower case, use the following command:

```
[raja@support ~]$ echo ${string,,}
```

```
linux for you
```

Now convert the same into upper case, as follows:

```
[raja@support ~]$ echo ${string^^}
```

```
LINUX FOR YOU
```

—Raja Genupula,
genupulas@ubuntu.com

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.