

```

root@devops1:~# sudo /opt/scalar-server/bin/scalar-server-wizard
[root@devops1 Desktop]# sudo /opt/scalar-server/bin/scalar-server-wizard
Please wait... Done!

Please double-check the following network settings.

--- Endpoint ---
Your instances need to be able to connect to Scalar for Scalar to manage them.
To that end, Scalar will advertise its endpoint to your instances.
That endpoint must resolve to this instance.

Scalar will advertise the following endpoint: "192.168.1.9"

Is this correct? If not, create (if necessary) and edit "/etc/scalar-server/scalar-server.rb", and add your endpoint.
For example: routing(endpoint host) = "my.endpoint.com"

--- IP Ranges ---
Scalar needs to connect to your instances to manage them.
To that end, Scalar will create Security Groups and whitelist its IP range in them.
At least one of those networks must include this instance's IP range.

Scalar will whitelist the following IP ranges: "192.168.1.9/32"

Is this correct? If not, create (if necessary) and edit "/etc/scalar-server/scalar-server.rb", and add your IP ranges.
For example: app(ip_ranges) = ["1.2.3.4/32", "5.6.7.8/32"]

--- Next Steps ---
If everything looks correct, run: "/opt/scalar-server/bin/scalar-server-ctl reconfigure"
If not, make the necessary changes, and re-run this script to check your configuration again.
[root@devops1 Desktop]#

```

Figure 9: Generating Scalar configuration files

```

root@devops1:~# sudo /opt/scalar-server/bin/scalar-server-ctl reconfigure
[root@devops1 Desktop]#

* supervisor service[httpd] action enable[2015-09-28T13:45:58-07:00] WARN: Cloning
resource attributes for execute[supervisorctl update] from prior resource (CHEF-3094)
[2015-09-28T13:45:58-07:00] WARN: Previous execute[supervisorctl update]: /opt/scalar-
server/embedded/cookbooks/supervisor/providers/service.rb:87:in "enable service"
[2015-09-28T13:45:58-07:00] WARN: Current execute[supervisorctl update]: /opt/scalar-
server/embedded/cookbooks/supervisor/providers/service.rb:87:in "enable service"

* template[/opt/scalar-server/etc/supervisor/conf.d/httpd.conf] action create (up
to date)
  * enabling supervisor service[httpd]
  * supervisor service[httpd] action start
    * Starting supervisor service[httpd]
    * execute[supervisorctl update] action nothing (skipped due to action nothing)
  * template[/opt/scalar-server/etc/supervisor/conf.d/httpd.conf] action create (up to
date)

Recipe: scalar-server::default
  * log[loader-group httpd always post] action write[2015-09-28T13:46:05-07:00] WARN:
Did not load recipe: group.httpd always post: recipe not found. OK to CONTINUE.

Recipe: scalar-server::group sysctl enabled post
  * execute[reload-sysctl] action nothing (skipped due to action nothing)
  * ruby_block[do-sysctl-conf] action run
    * execute the ruby block do-sysctl-conf
    * execute[reload-sysctl] action run
      * execute %$0$in/sysctl -p /etc/sysctl.conf || true

Recipe: scalar-server::default
  * log[loader-group sysctl always post] action write[2015-09-28T13:46:05-07:00] WARN:
Did not load recipe: group.sysctl always post: recipe not found. OK to CONTINUE.

Running handlers:
Running handlers complete
Chef Client finished, 85/262 resources updated in 155.755875063 seconds
[root@devops1 Desktop]#

```

Figure 10: Start all service components



Figure 11: Admin dashboard

following command in the terminal as shown in Figure 4:

```
curl -L https://packagecloud.io/install/repositories/
scalar/scalar-server-oss/script.rpm | sudo bash
```

It will download a repository file to `/etc/yum.repos.d/` as shown in Figure 5.




Figure 12: Scalar account creation




Figure 13: Account dashboard




Figure 14: Environment

Verify the contents of `scalar_scalar-server.repo` as shown in Figure 6.

Now install Scalar with the `sudo yum install -y scalar-server` command as shown in Figure 7.

It will take some time to download packages, and then it will install them as shown in Figure 8.

Now, generate configuration files such as the Apache configuration file, the PHP configuration file, etc, by using the command `sudo /opt/scalar-server/bin/scalar-server-wizard` as shown in Figure 9.

Review the default configuration and run `sudo /opt/scalar-server/bin/scalar-server-ctl reconfigure` to start all the components with the new configuration as shown in Figure 10.

Access the user interface of Scalar using `http://IP-OF-YOUR-SERVER/` as shown in Figure 11. The default admin password in `/etc/scalar-server/scalar-server-secrets.json`, under `app.admin` is `password`.

Go to **Accounts** and click on **Create**. Provide details such