

Figure 1: WordPress on PHP 7 (see Reference 2)




Figure 2: Frameworks performance under PHP 7 (see Reference 2)

```
//Equivalent to: $b = isset($a) ? 10 : 20
//isset() returns true if variable is set and not null.
```

The combined comparison operator, also known as the spaceship operator, is denoted by `<=>`. It returns zero if both the operands are equal, 1 if the left operand is greater and -1 if the right operand is greater.

```
<?php
$a <=> $b
```

The above expression will be resolved to 0 if \$a equals \$b, 1 if \$a is greater than \$b and -1 if \$b is greater.

Type declarations

Another feature introduced is to define the return type of functions and methods to avoid unintended return values. The code below states that `MyFunction()` returns a value which will be converted to bool automatically.

```
<?php
function MyFunction() : bool
{
    return 1;
```




Figure 3: PHP 7 against other dynamic languages (see Reference 2)

```
}
echo MyFunction();
```

PHP 7 introduces four new types of declarations for scalar types — integer, float, string and Boolean. By default, in a scalar type, if we pass a float value to an integer parameter, it will re-correct it to the integer without outputting any warning or error.

```
<?php
function add(int $a, int $b) : int
{
    return $a + $b;
}

echo add(1, 2); // 3
echo add(1.5, 2.5); // 3 as floats are truncated by default
```

Anonymous classes

Anonymous class (class without a name) is another feature provided which is already available in Java and other object-oriented languages. It has the same syntax as the normal class that was written in PHP but without a name. It can be used in case the class does not need to be documented.

```
<?php
var_dump(new class()
{
    public function MyFunction()
    {
        //code
    }
});
```

Import from the same namespace

This Group Use Declaration feature allows us to import many classes from the same namespace with a single line.

Continued on page 87...