

and destination folder where a copy of the website will be stored.

—Mohammed Rampurawala,
mohammed.rampurawala@hotmail.com



No need to rewrite the command

Sometimes we forget to write `sudo` at the beginning of a command and then have to rewrite the whole command again, starting with `sudo`. To avoid this, you need to use “!!” after `sudo` and it will put the last command after `sudo`.

As an example, the following command...

```
#apt-get install gcc
#sudo !!
```

...will execute as follows:

```
#sudo apt-get install gcc
```

—Dilip Pandit, panditdilip@gmail.com



View manual pages while using Vim Editor

To be able to read the man pages while working on a file in Vim Editor, you do not need to come out of Vim. Just bring the cursor on the word and press K (capital), and you will be taken to the man page associated with the word.

To go to a specific section (e.g., system calls, second section) of the manual page, bring the cursor onto the word and press 2K; it opens the second section of the manual pages for that word.

—Raveendra Reddy Padala,
raveendrapadala@gmail.com



Rename and re-size images

Fond of your new camera but can't put up with the terrible names of the images? Do you also want to prepare these for publishing on the Web? A simple bash script is what you need:

```
#!/bin/sh
counter=1
root=mypict
resolution=400x300
for i in `ls -1 $1/*.jpg`; do
    echo "Now working on $i"
    convert -resize $resolution $i
    ${root}.${counter}.jpg
    counter=`expr $counter + 1`
done
```

Save the script in a file called `picturename.sh` and make it executable with the following command:

```
chmod u+x picturename.sh
```

Then store it somewhere in your path. Now, if you have a bunch of `.jpg` files in the directory `/path/to/pictdir`, all you have to do is execute the following command:

```
picturename.sh /path/to/pictdir
```

...and in the current directory, you'll find `mypict_1.jpg`, `mypict_2.jpg`, etc, which are the re-sized versions of your original pictures. You can change the script according to your needs, or, if you're just looking for super-simple image resizing, try looking at the `mogrify` command with its geometry parameters.

—Albert Levay, chrishlove55@gmail.com



Know the temperature of your hard disk in Linux

You can read your hard disk's temperature if the disk has an inbuilt temperature sensor. `hddtemp` is a tool that will help you to read the temperature. It will give you the temperature of your hard drive by reading the Self-Monitoring Analysis and Reporting Technology (S.M.A.R.T.) information on drives that support this feature. Only modern hard drives have a temperature sensor.

Step 1: Install `hddtemp` by typing the following command:

```
#yum install hddtemp
```

...or whatever your package manager supports.

Step 2: In the terminal, type the following command:

```
#hddtemp /dev/sda
```

Here `/dev/sda` is the hard disk that we are trying to get the temperature of.

—Bhargab Choudhury,
bhargabchoudhury24@gmail.com

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.